



(anteriormente IRIX LSM)

IRIX L 130-2

Greases

DESCRIPTION

IRIX L 130-2 is a multi-purpose, extreme-pressure grease formulated from premium mineral base oils and a Lithium thickener. The NLGI grade 2 makes it suitable for a wide range of general-purpose applications.

APPLICATIONS

IRIX L 130-2 is suitable for a wide range of general-purpose lubrication applications ranging from bearings to cables, chains and other linkages. Also suitable as a multipurpose chassis, pin and bushing grease.

Classification:

- ISO 12924: L-XBCHB2
- DIN 51502: KP2K-20

ADVANTAGES

- Excellent protection against corrosion.
- Excellent extreme-pressure performance.
- Excellent wear protection.
- Very good adhesion.
- Very good stability in service and storage.
- Insoluble in water.



TECHNICAL INFORMATION

TECHNICAL CHARACTERISTICS	UNITS	METHOD	IRIX L 130-2
Base oil	-		
Color	-	Visual	Amber
Texture	-		Smooth
Thickener	-		
NLGI Grade	-	ASTM D217	2
Dropping point	°C	IP 396	190.0
Base oil viscosity at 40°C	mm²/s	ASTM D7152	130.0
Base oil viscosity at 100°C	mm²/s	ASTM D7152	11.0
Penetration 60 strokes	1/10 mm	ISO 2137	280
EMCOR distilled water	-	ISO 11007	0-0
EMCOR salt water	-	ISO 11007	< 2-2
Water resistance at 90°C	-	DIN 51807:1	0-90
4 Ball test - Weld load	kg	ASTM D2596	285
Operating range temperature	-		-20°C to +140°C

These characteristics are given only for information and can be updated over time.

SERVICES AND EQUIPMENT

In addition to its product ranges, MotulTech can provide tools and services for the maintenance and monitoring of your lubricants. Please contact your technical sales representative for more information.

Important Notice

Information disclosed in this technical data sheet is based on MOTUL's experience and know-how in the development and manufacture of lubricants and other chemical products according to the current state of knowledge.

Any chemical product must be used in the intended application and in accordance with the recommendations provided in its safety data sheet freely consultable via the site <https://www.quickfds.com/fr/>. The performance of our products may be influenced by a series of factors, including conditions of use, application methods, operational environment, pretreatment of components, possible external contamination, etc ... For these reasons, universal recommendation of our products is impossible. The information in the technical data sheet represents general, non-binding guidelines and is given for guidance only. No express or implied warranty is given regarding the properties of the product or its suitability for a given application.

Therefore, we recommend consulting an application engineer to discuss application conditions and product performance criteria before use. It is the user's responsibility to test the functional suitability of the product and to use it under appropriate safety conditions. Our products are subject to continuous improvement with the aim of improving performance or bringing them into compliance with any new and possible regulations concerning them. We reserve the right to change our product lines, our products and their manufacturing processes and any provisions of our publications at any time without notice. This technical sheet cancels and replaces all previous editions.

We expressly draw the attention of any user to the fact that our product has not been designed and tested for use in the field of aeronautics as an "onboard" product or in the field of nuclear power production. Any use that may be made of the product in one of the aforementioned sectors will be under the exclusive responsibility of the user. Any reproduction, whatever its form, requires the prior written consent of MOTUL. All rights reserved.