

**Greases & Pastes****TYPE OF USE**

**IRIX L 150-2 MO** is a lithium thickened lubricating grease based on mineral oil. The grease contains antioxidants, corrosion inhibitors, EP/AW additives and MoS<sub>2</sub>.

**PERFORMANCES**

**IRIX L 150-2 MO** is a high quality multipurpose MoS<sub>2</sub> grease that can be used in both industrial and automotive applications. The molybdenum disulphide gives extra protection in applications with slow moving or oscillating bearings. Lubricating greases with solids are not suitable for rolling bearings at high speed.

Classification:

- ISO 12924: L-XBCHB2
- DIN 51502: KPF2K-30

**PROPERTIES**

Color	Visual	Black
Drop point	IP 396	> 185 °C
Base oil viscosity at 40°C	ISO 12185	150.0 mm <sup>2</sup> /s
NLGI Grade	ASTM D217	2
Thickener		Lithium Simple
Temperature range		-30°C to 120°C (max 130°)

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty.

04/23

MOTUL Deutschland GmbH - Butzweilerhofallee 3 - 50829 - Cologne - +49(0)221/67003-0 - +49(0)221/67003-199 - info@motul.de - http://www.motul.com