

**IRIX LSM 151****Extreme Pressure Grease  
Mineral****TYPE OF USE**

**IRIX LSM** is a multi-purpose, extreme-pressure range of greases formulated from premium mineral base oils and a Lithium thickener.

**PERFORMANCES**

STANDARDS                      DIN 51 502 KP1K-20  
  ISO 12924 L-XBCIB1

**IRIX LSM** grease can be used to lubricate bearings, gears and all mechanical units operating under high loads.

- **Grades 0-00:** Reducers, centralised greasing, gears in crankcases, various parts working in a cold atmosphere, all soft EP grease uses.
- **Grade 1:** Centralised greasing.
- **Grade 2:** Suitable for a wide range of general-purpose lubrication applications ranging from bearings to cables, chains and other linkages. Also suitable as a multipurpose chassis, pin and bushing grease.
- **Grade 3:** Truck hubs, very loaded sleeves.

**PROPERTIES**

Color	Visual	Amber
Viscosity at 40°C (104°F)		130.0 mm <sup>2</sup> /s
TIMKEN Test - Load		≥ 40 lbs
NLGI Grade		1
Thickener		Lithium Simple
Penetration 60 strokes		<0.6 mm Wear scar / 285 kg Weld load
Temperature range		-20 to +140 °C

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty. Made in FRANCE

MOTUL - 119 Bd Félix Faure - 93303 - AUBERVILLIERS CEDEX - BP 94 - Tel: 33 1 48 11 70 00 - Fax: 33 1 48 33 28 79 - www.motul.com