

MOTUL IRIX TECH 300



زيت تشحيم متعدد الأغراض عالي الأداء
Technosynthese - ليثيوم مركب - NLGI 2 - ضغط عالي

أنواع الاستخدام

شحم متعدد الأغراض عالي الأداء موصى به لتشحيم محامل الأسطوانة، المحامل العادية، محامل الدفع، التروس، المحركات الكهربائية، الرفعات، البطانات، محامل العجلات، الوصلات العالمية، الوصلات الكروية، تشحيم الهيكل في السيارات الثقيلة والخفيفة، معدات تنسيق الحدائق، الزراعة، الدراجات النارية ومعدات الرياضات القوية التي تعمل في ظل ظروف قاسية. درجات حرارة التشغيل للتشحيم طويل الأمد: من -30 درجة مئوية / -22 درجة فهرنهايت إلى +150 درجة مئوية / +302 درجة فهرنهايت وحتى +200 درجة مئوية / +392 درجة فهرنهايت في الذروة.

مستويات الاداء

شحم تكنوسينثيس® Technosynthese® عالي الجودة مركب بصابون الليثيوم المعقد، وضغط شديد، ومضافات مضادة للتآكل، ومضادة للأكسدة، ومضادة للتآكل. مزايا IRIX TECH 300: - أداء ممتاز في درجات الحرارة العالية: نقطة الانصهار عند +260 درجة مئوية / +500 درجة فهرنهايت تسمح بالتشحيم المستمر حتى +150 درجة مئوية / +302 درجة فهرنهايت ولفترات قصيرة حتى +220 درجة مئوية / +428 درجة فهرنهايت - خصائص تدفق بارد ممتازة: حد القابلية للضخ -30 درجة مئوية / -22 درجة فهرنهايت - قدرة تحميل عالية وفقًا لنتائج اختبار FAG FE-9 - حماية ممتازة ضد التآكل - مقاومة جيدة للماء مع تعزيز الالتصاق تشحيم طويل الأمد / تقليل تكاليف الصيانة التسمية DIN 51502: KP 2 P-30

المواصفات

Green	Visual	Color
(C 500 °F° 260 <	DIN ISO 2176	Drop point
mm ² /s 100.0	DIN 51562	Base oil viscosity at 40°C
mm ² /s 12.0	DIN 51562	Base oil viscosity at 100°C
NLGI 2	DIN 51818	Consistency grade
150 / 1	ASTM D4048	Copper Strip Corrosion
90 / 1	DIN 51807 T1	Water washout

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development. br>

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty. Made in FRANCE

06/25

- MOTUL - 119 Bd Félix Faure - 93303 - Aubervilliers Cedex - BP 94 - FRANCE - Tel: 33 1 48 11 70 00 - Fax: 33 1 48 33 28 79

motul.com

MOTUL IRIX TECH 300



زيت تشحيم متعدد الأغراض عالي الأداء
Technosynthese - ليثيوم مركب - NLGI 2 - ضغط عالي

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development. br>

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty. Made in FRANCE

- MOTUL - 119 Bd Félix Faure - 93303 - Aubervilliers Cedex - BP 94 - FRANCE - Tel: 33 1 48 11 70 00 - Fax: 33 1 48 33 28 79