

## **MDM 30/40**

Lubricant for Motorboat 4 stroke engines Turbocharged or not SAE 30/40

### TYPE OF USE

Specially formulated for Diesel inboard engines. Recreational and professional engine boats, generators...

Suitable with Diesel engines, turbocharged or not : Boats, Generators, Trucks, Bulldozers, Civil Engineering machines, Farm machinery...

Specially recommended for engines working with Diesel fuels with high Sulfur content (0.8% to 1.5%) mainly used in Africa, Asia, Middle East and for high cubic capacity engines.

Suitable for reduction gear system when a monograde engine oil is recommended.

#### **PERFORMANCES**

Particularly efficient when using fuel with high percentage level of Sulfur (0.8% to 1.5%).

The high TBN is representative of detergency / dispersivity level of the oil, and allows neutralizing acid residues created by fuel combustion. The quantity of acid residues is proportional to the quantity of fuel sulfur content.

Excellent anti-wear properties for a longer engine lifetime.

Anti-oxidizing, Anti-corrosion, Anti-rust, Anti-foam.

#### **RECOMMENDATIONS**

Oil change: according to manufacturers' requirements and oil test results.

#### **PROPERTIES**

Viscosity grade	SAE J 300	30/40
Density at 20°C (68°F)	ASTM D1298	0.895
Viscosity at 40°C (104°F)	ASTM D445	157.6 mm <sup>2</sup> /s
Viscosity at 100°C (212°F)	ASTM D445	15.8 mm²/s
Viscosity Index	ASTM D2270	103.0
Pour point	ASTM D97	-18.0 °C / -0.4 °F

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty. Made in FRANCE

MOTUL - 119 Bd Félix Faure - 93303 - AUBERVILLIERS CEDEX - BP 94 - Tel: 33 1 48 11 70 00 - Fax: 33 1 48 33 28 79 - www.motul.com



**MDM 30/40** 

Lubricant for Motorboat 4 stroke engines Turbocharged or not SAE 30/40

TBN ASTM D2896 20.0



# **MDM 30/40**

Lubricant for Motorboat 4 stroke engines Turbocharged or not SAE 30/40

STANDARDS				
API	CE / SE			
CCMC	D-4			
MIL-L	-2104 E Engines			
OE PERFORMANCES				
CATERPILLAR	DEO Engines, TO-2 Transmissions			
MOTEURS BAUDOUIN.S.A	BAUDOIN Engines and Gearboxes			
SAURER	Engines			
WÄRTSILÄ	SACM DIESEL / POYAUD			
PRODUCTS				
BWSC	Moteurs			
POYAUD	/ WARTSILA SACM DIESEL			
SACM DIESEL	WARTSILA / POYAUD			