



MOTUL MOTOCOOL EXPERT -37°C

Motorbike ready to use cooling liquid
Anti-corrosion and anti-freeze
Protection -37°C / -35°F
Nitrite free / Amine free / Borate free

TYPE OF USE

MOTUL MOTOCOOL EXPERT -37°C is a ready to use cooling liquid, anti-freeze and anti-corrosion for motorbike cooling systems.

Based on monoethyleneglycol, MOTOCOOL EXPERT -37°C contains reinforced hybrid anti-corrosion additives using hybrid organic / non organic mix additive technology, named Hybrid Tech. This product is especially suitable for light aluminum alloys used in motorbike engine designs.

PERFORMANCES

STANDARDS AFNOR NF R 15-601
 ASTM STANDARD D3306
 BRITISH STANDARD BS 6580
 JAPANESE STANDARD JIS K2234

Protects the cooling system from freezing (-37°C / -35°F) and metallic parts from corrosion.

Provides an excellent thermal exchange to improve engine cooling efficiency.

Protects bike engines from overheating and from high running temperatures.

Outstanding anti-corrosion and anti-cavitation properties that remain while aging.

Seals, rubber pipes and plastic parts friendly.

Anti-foam properties.

Contains a bitter-tasting agent to prevent from ingesting: coolants and antifreezes have a sweet taste but are harmful if swallowed.

RECOMMENDATIONS

Ready to use, do not add any water.

Drain intervals: Refer to the manufacturers' recommendation.

This product should not be used to protect drinking water systems against freezing.

STORAGE: Avoid light exposure during storage.

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development. br\>

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty. Made in FRANCE

MOTUL - 119 Bd Félix Faure - 93303 - Aubervilliers Cedex - BP 94 - FRANCE - Tel: 33 1 48 11 70 00 - Fax: 33 1 48 33 28 79 - www.motul.com



MOTUL MOTOCOOL EXPERT -37°C

Motorbike ready to use cooling liquid
Anti-corrosion and anti-freeze
Protection -37°C / -35°F
Nitrite free / Amine free / Borate free

PROPERTIES

Color	Visual	Yellow
Density at 20°C (68°F)	ASTM D1121	1.071
pH	ASTM D1287	8.1
Freezing point		-37.0 °C / -35.0 °F
Boiling point	ASTM D1120	109.0 °C / 223.0 °F