

MOTUL GASMA SAE 40

Industrial engine oil

DESCRIPTION

MOTUL GASMA is a high performance engine oil dedicated to the latest generation 4-stroke gas engines designed with aluminium pistons requiring low ash oil.

MOTUL GASMA technology reduces sludge deposit and plug fouling leading to increased spark plug life so longer operating life and lower maintenance costs.

ADVANTAGES

- Reduced valve wear
- Very low piston deposit and sludge formation
- Extended spark plugs life
- Optimized drain interval and lifecycle cost
- Low maintenance costs

TECHNICAL INFORMATION

Characteristics	Method	Units	Norms
SAE Grade			40
Density @ 15°C	ASTM D1298		0.88
Viscosity @ 40°C	ASTM D445	cSt	126
Viscosity @ 100°C	ASTM D445	cSt	13.55
Sulfated Ash	ASTM D874	% wt	0.5
Flash point	ASTM D92	°C	266
Pour point	ASTM D97	°C	-36
TBN	ASTM D2896	mg KOH / g	5.5

SPECIFICATIONS / APPROVALS

MOTUL GASMA meets or exceeds the most common specifications and OEM requirements:

- Caterpillar - 3516 TALE engines
- MWM – TCG 2016 V12 and TCG 2020 V16 engines in Natural Gas

MOTUL GASMA received approvals from:

- GE Jenbacher Type 2, Type 3, Type 4 (versions A&B), Type 6 (versions C&E) Natural Gas (Class A)
- MAN M 3271-2 (Natural gas)
- MWM – Natural gas

APPLICATION

MOTUL GASMA is a high performance engine oil for latest generation 4-stroke, spark-ignition stationary gas engines.

SERVICE AND EQUIPMENT

In addition to its product ranges, Motul can provide tools and services for the maintenance and in-use monitoring of your lubricants. Please contact your technical sales representative.

IMPORTANT NOTICE

All information and rules about health, safety and the environment are mentioned on the safety data sheet. It provides information about risks, safety procedures and first aid emergency rules. It clarifies all procedures to implement in the case of an accidental spillage, and for the disposal of the product and its effects on the environment.

Our product contains natural additives which are likely to modify the colour of the concentrates without altering its performance. The specifications of our products are definite only at the time of order, and are subject to our general sale and guarantee conditions. To give our customers the latest technical developments, the general characteristics of our products may vary. The safety data sheet of this product is available at www.motul.com