



MOTUL GASMA SAE 40

Industrial Engine Oil

Mineral

TYPE OF USE

MOTUL GASMA is a high-performance engine oil for the latest generation of 4-stroke gas engines with aluminum pistons that require a low-ash oil.

MOTUL GASMA technology reduces sludge deposits and spark plug fouling, resulting in longer spark plug life and lower maintenance costs.

PERFORMANCES

MOTUL GASMA is a high-performance engine oil for latest generation 4-stroke, spark-ignition stationary gas engines.

Advantages:

- Reduced valve wear
- Very low piston deposit and sludge formation
- Extended spark plug life
- Optimized drain interval and lifecycle cost
- Low maintenance costs

PROPERTIES

Viscosity grade	SAE J 300	40
Density at 20°C (68°F)	ASTM D1298	0.88
Viscosity at 40°C (104°F)	ASTM D445	120.0 cSt

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty.

MOTUL - 119 Bd Félix Faure - 93303 - Aubervilliers Cedex - BP 94 - FRANCE - Tel: 33 1 48 11 70 00 - Fax: 33 1 48 33 28 79 - www.motul.com

motul.com

09/26



MOTUL GASMA SAE 40

Industrial Engine Oil

Mineral

Viscosity at 100°C (212°F)	ASTM D445	13.8 cSt
Viscosity Index	ASTM D2270	114
Pour point	ASTM D97	-18.0 °C / 0.0 °F
Sulfated Ash	ASTM D874	% weight 0.50
TBN	ASTM D2896	5.3 mg KOH/g
Flash point	ASTM D92	276.0 °C / 529.0 °F

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty.

MOTUL - 119 Bd Félix Faure - 93303 - Aubervilliers Cedex - BP 94 - FRANCE - Tel: 33 1 48 11 70 00 - Fax: 33 1 48 33 28 79 - www.motul.com

Industrial Engine Oil**Mineral**

STANDARDS	
INNIO Waukesha	275GL/GL+ series, APG series (16V150LTD), VGF series, VHP series
MAN	M 3271-2 (Natural Gas)
WÄRTSILÄ	1641206414704 – engine types 175SG, 220SG, 25SG, 28SG, 31SG, 34SG, 50SG, 20DF, 31DF, 32DF, 34DF, 46DF and 50DF with natural gas as main fuel
	CATERPILLAR – CG132, CG132B, CG170, CG170B, CG260, MWM – TCG 2016, TCG 3016, TCG 2020, TCG 3020, TCG 2032, TCG 2032B series
OEM PERFORMANCES	
Cummins	CES 14615
INNIO Jenbacher	Type 2 all versions (class A natural gas), Type 3 all versions (class A natural gas), Type 4, version B (class A natural gas), Type 4, version D (class A natural gas), Type 6, version C (class A natural gas), Type 6, version E (class A natural gas)

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty.