

Industrial engine oil**Mineral****TYPE OF USE**

MOTUL GASMA SP is a high performance engine oil dedicated to latest generation 4-stroke gas engines designed with steel pistons and requiring mid ash oil.

It is also suitable for 4-stroke gas engines designed with aluminium pistons.

MOTUL GASMA SP new additive technology provides superior valve recession protection. Its high quality base oils helps preventing the build-up of oxidation and nitration.

PERFORMANCES

MOTUL GASMA SP is a high performance engine oil for latest generation 4-stroke, sparkignition stationary gas engines designed with steel pistons.

PROPERTIES

Viscosity grade	SAE J 300	40
Density at 20°C (68°F)		0.87
Viscosity at 40°C (104°F)	ASTM D445	114.2 cSt
Viscosity at 100°C (212°F)	ASTM D445	12.9 cSt
Pour point	ASTM D97	-21.0 °C
Sulfated Ash	ASTM D874	% weight 0.65
TBN	ASTM D2896	4.6 mg KOH/g
Flash point	ASTM D92	260.0 °C

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty.

MOTUL - 119 Bd Félix Faure - 93303 - Aubervilliers Cedex - BP 94 - FRANCE - Tel: 33 1 48 11 70 00 - Fax: 33 1 48 33 28 79 - www.motul.com

motul.com

07/26

Industrial engine oil**Mineral**

STANDARDS	
CATERPILLAR	CG
Innio Jenbacher	special gas applications, Type 2 all versions (class A natural gas), Type 3 all versions (class A natural gas), Type 4, version B (class A natural gas), Type 4, version C (class A natural gas), Type 4, version D (class A natural gas), Type 4, version E (class A natural gas), Type 6, version C (class A natural gas), Type 6, version E (class A natural gas), Type 6, version F (class A natural gas), Type 6, version J (class A natural gas)
MWM	TCG
Rolls Royce Bergen	B36:45, B35:40, C26:33 and K-type gas engine
OEM PERFORMANCES	
MTU	gas engines Series 4000 L64 / L64FNER / T24N and 4000 L61 / L62 / L63 using natural gas

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty.