

MOTUL MOTYLGEAR 75W-90



زيت تروس ومحور التفاضل Technosynthese تقنية

أنواع الاستخدام

موصى به بشكل خاص لصناديق التروس التي يصعب تغييرها و/أو صناديق التروس الصاخبة. جميع أنظمة النقل الميكانيكية، صناديق التروس المتزامنة أو غير المتزامنة، صندوق التروس/الفرق، صناديق التروس التحويلية والفرق الهيدروية بدون أنظمة انزلاق محدودة، التي تعمل تحت الصدمات، الأحمال الثقيلة والسرعة المنخفضة أو الأحمال المعتدلة والسرعة العالية.

مستويات الاداء

زيت تشحيم تكنوسينثيس® Technosynthese® "الضغط الشديد" التخليقي لحماية فعالة ضد التآكل معززة بقاعدة تخليقية لمقاومة أفضل في درجات الحرارة العالية وعمر أطول. يبقى في درجة لزوجة 90 بعد اختبار القص KRL لمدة 20 ساعة كما هو مطلوب من قبل معيار SAE J306. قوة تشحيم عالية جدًا تقلل الاحتكاك والتآكل. درجة لزوجة 90 في درجات الحرارة العالية لتوفير مقاومة ممتازة لطبقة الزيت في درجات الحرارة العالية و/أو لتقليل ضوضاء النقل. سائل في درجات الحرارة المنخفضة للسماح بتغيير التروس بسهولة عندما يكون صندوق التروس باردًا. جهد أقل مطلوب على ذراع التروس لتغيير التروس لتحسين راحة القيادة. مناسب لأي نوع من الأختام والمواد الصفراء المستخدمة في تصميم صناديق التروس. مضاد للتآكل، مضاد للرغوة.

التوصيات

تغيير الزيت: وفقًا لمتطلبات الشركات المصنعة وتعديلها وفقًا لاستخدامك الشخصي.

المواصفات

75W-90	SAE J 300	Viscosity grade
0.855		(Density at 20°C (68°F
mm²/s 114.1	ASTM D445	(Viscosity at 40°C (104°F
mm²/s 18.1	ASTM D445	(Viscosity at 100°C (212°F
176.0	ASTM D2270	Viscosity Index
C / -60.0 °F° 51.0-	ASTM D97	Pour point
C / 390.0 °F° 199.0	ASTM D92	Flash point

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development. br>

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty. Made in FRANCE

06/25

- MOTUL - 119 Bd Félix Faure - 93303 - Aubervilliers Cedex - BP 94 - FRANCE - Tel: 33 1 48 11 70 00 - Fax: 33 1 48 33 28 79

motul.com

MOTUL MOTYLGEAR 75W-90



زيت تروس ومحور التفاضل
Technosynthese تقنية

STANDARDS	
GL-4, GL-5	API
D 2105	MIL-L

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development. br>

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty. Made in FRANCE

- MOTUL - 119 Bd Félix Faure - 93303 - Aubervilliers Cedex - BP 94 - FRANCE - Tel: 33 1 48 11 70 00 - Fax: 33 1 48 33 28 79