



MT STORE PROTECT

Dewatering corrosion preventive fluid

SOLVENT BASE

DESCRIPTION

MT STORE PROTECT is a waxy rust preventative fluid, with dewatering properties. The product is formulated on the latest generation of barium-free protection additives. **MT STORE PROTECT** provides excellent dewatering & demulsifying performance combined with protection against acidic or alkaline contaminations.

MT STORE PROTECT is recommended for medium to long-term protection of metal parts, even in severe conditions (up to 18 months indoors and up to 6 months outdoors under shelter). The product leaves a thin waxy film on the components, it is ideal for protecting machined parts before storage or transport.

APPLICATIONS

MT STORE PROTECT is typically applied by dipping process. The product can also be spraying or applied by brush.

MT STORE PROTECT can be applied on clean and dry parts or directly on damp metal parts. It eliminates residual water from previous operations (soluble machining, washing, etc.) while protecting them from corrosion.

ADVANTAGES

- Medium to long term protection even for severe conditions
- Excellent water displacement and demulsifying properties
- Fast drying behaviour
- Barium free
- Low smell.



TECHNICAL INFORMATION

TECHNICAL CHARACTERISTICS	UNITS	METHOD	MT STORE PROTECT
Color	-		Light Brown
Density	-	ISO 12185	0.815
Viscosity at 40°C	mm ² /s	ASTM D445	3.1
Flash point	°C	ASTM D92	114
Corrosion Protection	months		18 months indoors and 6 months outdoors under shelter
Residual Film Thickness	µm		2.0
Coverage	m ² /kg		140.0

These characteristics are given only for information and can be updated over time.

HEALTH AND SAFETY

- Without barium or hazardous components
- High flash point : 114 °C

INSTRUCTIONS

Degreasing the protective layer :

If necessary, the residual film of **MT STORE PROTECT** can be easily removed using alkaline detergents (**SAFKLEEN** range) or solvents (**SAFCO KLEEN** range).

Storage Conditions :

To ensure any deterioration of the product, always store the product between 5°C and 40°C. Keep away from direct sunlight and store in a covered, cool and dry area.

SERVICES AND EQUIPMENT

In addition to its product ranges, MotulTech can provide tools and services for the maintenance and monitoring of your lubricants. Please contact your technical sales representative for more information.



Important Notice

Information disclosed in this technical data sheet is based on MOTUL's experience and know-how in the development and manufacture of lubricants and other chemical products according to the current state of knowledge.

Any chemical product must be used in the intended application and in accordance with the recommendations provided in its safety data sheet freely consultable via the site <https://www.quickfds.com/fr/>. The performance of our products may be influenced by a series of factors, including conditions of use, application methods, operational environment, pretreatment of components, possible external contamination, etc ... For these reasons, universal recommendation of our products is impossible. The information in the technical data sheet represents general, non-binding guidelines and is given for guidance only. No express or implied warranty is given regarding the properties of the product or its suitability for a given application.

Therefore, we recommend consulting an application engineer to discuss application conditions and product performance criteria before use. It is the user's responsibility to test the functional suitability of the product and to use it under appropriate safety conditions. Our products are subject to continuous improvement with the aim of improving performance or bringing them into compliance with any new and possible regulations concerning them. We reserve the right to change our product lines, our products and their manufacturing processes and any provisions of our publications at any time without notice. This technical sheet cancels and replaces all previous editions.

We expressly draw the attention of any user to the fact that our product has not been designed and tested for use in the field of aeronautics as an "onboard" product or in the field of nuclear power production. Any use that may be made of the product in one of the aforementioned sectors will be under the exclusive responsibility of the user. Any reproduction, whatever its form, requires the prior written consent of MOTUL. All rights reserved.