

**Continuously Variable Transmission (CVT) Fluid fitted with chain or belt
Technosynthese®**

TYPE OF USE

High performance synthetic Technosynthese® fluid specially engineered for Continuously Variable Transmission (CVT) gearbox type.

Suitable for use in a wide range of vehicles fitted with CVT gearboxes using either chain/pulleys or belt/pulleys design.

Especially suitable for vehicles from American car makers GM, FORD, CHRYSLER,..., Asian car makers HONDA, HYUNDAI, KIA, LEXUS, INFINITI, MITSUBISHI, NISSAN, SUBARU, TOYOTA,... or European car makers AUDI, BMW, CITROËN, MERCEDES, PEUGEOT, RENAULT, ...

Attention, not recommended for CVT unit fitting hybrid vehicles.

Before use always refer to the owner manual or handbook of the vehicle.

PERFORMANCES

MOTUL MULTI CVTF is a high tech multi vehicles CVT fluid suitable for a wide range of CVT-equipped passenger cars, including belt-CVT and chain-CVT design.

Thanks to its exclusive and dedicated synthetic formula, MULTI CVTF:

- Allows fuel economy for cars fitted with CVT automatic gearboxes by providing optimum metal-to-metal friction.
- Provides high anti-shudder performance to avoid engine vibrations for increased comfort.
- Protects gears that are more and more numerous, compact and heavily loaded.
- Gives superior automatic transmission response through smooth shift feel and reduced shift time lag.
- Improves CVT reaction at cold temperature.
- Extends life time duration due to high shear stability at hot temperature and high oxidation resistance.
- Increases wear protection of belt, chain and pulleys.
- Anti-corrosion, anti-foam.



MOTUL MULTI CVTF

Continuously Variable Transmission (CVT) Fluid fitted with chain or belt
Technosynthese®

RECOMMENDATIONS

Can be mixed only with similar lubricants.

Oil change: according to manufacturer's recommendations and adapt according to your own use.

Not recommended for CVT unit fitting hybrid vehicles.

Before use always refer to the owner manual or handbook of the vehicle.

PROPERTIES

Color	Visual	Blue
Density at 20°C (68°F)	ASTM D1298	0.843
Viscosity at 40°C (104°F)	ASTM D445	34.8 mm²/s
Viscosity at 100°C (212°F)	ASTM D445	7.3 mm²/s
Viscosity Index	ASTM D2270	182.0
Flash point	ASTM D92	220.0 °C / 428.0 °F

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty.

MOTUL - 119 Bd Félix Faure - 93303 - Aubervilliers Cedex - BP 94 - FRANCE - Tel: 33 1 48 11 70 00 - Fax: 33 1 48 33 28 79 - www.motul.com

Continuously Variable Transmission (CVT) Fluid fitted with chain or belt
Technosynthese®

OEM PERFORMANCES	
AUDI	G 052 180, G 052 516, Multitronic, TL 52 116, TL 52 180, TL 52 516
BMW	83 22 0 136 376, 83 22 0 429 154, EZL 799, EZL 799 A
CHERY	CVT, WCF-1
CHRYSLER	CVTF+4, NS-2
CITROËN	9735 EF, Elfmatic CVT, Elfmatic CVT MV
DAIHATSU	AMMIX CVTF DFE, AMMIX CVT Fluid DC, AMMIX CVT Fluid DFE, CVTF 3320, CVT Fluid DFC, Fluid TC
DODGE	05191184AA, CVTF+4, NS-2
DS (CAPSA)	9735 EF, Elfmatic CVT, Elfmatic CVT MV
FIAT	Tutela Car CVT N.G
FORD	CVT23, CVT30, MERCON C, WSS-M2C928-A, WSS-M2C933-A, XT-7-QCFT
GENERAL MOTORS	1940713, 1940714, CVTF I-Green2, DEX-CVT, HP CVTF 95529854, VT40
HONDA	08200-9006, 08200-HCF-2, 0826099905HE, 087009006, HMMF (Honda Multi Matic Fluid) for CVT models only, without wet starting clutch, CVT-F, Genuine CVT Fluid, HCF-2, Ultra HEVF-Type 1, Z-1 (CVT models only, without starting clutch, not for Honda Jazz & Fit MY 2001-2007)
HYUNDAI	CVT-1, Genuine CVTF, SP-CVT 1, SP III (CVT models only)
INFINITI	999MP-NS200P, NS-1, NS-2, NS-3
JEEP	05191184AA, CVTF+4, NS-2, VTF
KIA	CVT-1, SP-CVT 1, SP III (CVT models only)
LEXUS	CVTF 3320, CVT FE, Fluid FE, Fluid TC
LIFAN	CVT
MAZDA	CVTF 3320, JWS 3320
MERCEDES-BENZ	A 001 989 46 03, MB 236.20
MG	EM-CVTF
MINI	83 22 0 136 376, 83 22 0 429 154, COOPER EZL 799 A, EZL 799, ZF CVT V1
MITSUBISHI	CVTF ECO J4, Dia Queen CVTF-J1 (MMC Diaqueen CVT Fluid J1), Dia Queen CVTF-J4, Dia Queen CVTF-J4+ (MMC Diaqueen CVT Fluid J4 and J4+), MZ313973, SP III (CVT models only)
NISSAN	999MP-NS200P, KTF-1, N-CVT, NS-1, NS-2, NS-2V, NS-3
OPEL	7-speed CVT, HP CVTF 95529854, VT40
PERODUA	D-CVT
PEUGEOT	9735 EF, Elfmatic CVT, Elfmatic CVT MV
RENAULT	CVT CK/SK/FK, Elfmatic CVT, Elfmatic CVT MV
ROVER	EM-CVTF, Unipart Transmatic ATF
SATURN	22688912, DEX-CVT
SEAT	G 052 180, G 052 516

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty.

Continuously Variable Transmission (CVT) Fluid fitted with chain or belt
Technosynthese®

SUBARU	CV30, CVT III Fluid, CVT TR580, CVT TR690, ECVT, High Torque CVT, High Torque CVTF-LV, iCVTF, i-CVTF FG, K0421Y0700, K0425Y0710, K0425Y0711, Lineartronic chain CVT 3 Fluid, Lineartronic chain CVT and CVT II Fluid, Lineartronic CVTF, Lineartronic High Torque (HT) CVT Fluid, Lineartronic II, NS-2, SOA748V0300
SUZUKI	CVTF 3320, CVTF 4401, CVTF TC, CVT Green 1, CVT Green 1V, CVT Green 2, NS-2
TOYOTA	CVTF 3320, CVTF FE, TC
VAUXHALL	7-speed CVT, HP CVTF 95529854, VT40
VOLVO	CVTF 4959
VW	G 052 180, G 052 516
ZOTYE	RDCF01, RDCF02, CVTs
PRODUCTS	
ELF	matic CVT, matic CVT MV
ESSO	EZL 799, FN1975
FUJIIYUKO	i-CVTF FG
IDEMITSU	CVTF-EX1
MOBIL	CVTF 3320
MOPAR PARTS	CVTF+4, CVTplus4
PETRONAS LUBRICANTS	Tutela Car CVT N.G
PSA Groupe	9735 EF, Elfmatic CVT, Elfmatic CVT MV
PUNCH	CVTF-EX1
SHELL	Green 1V, SL 2100

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty.