

**MULTI GREASE 150**

**Multipurpose Grease  
Lithium  
NLGI 2 – Extreme Pressure**

**TYPE OF USE**

Multipurpose grease for roller bearings, articulations, bearings, hubs, ball joint, water pumps...  
Car, Motorbike, Marine, Transport, Civil engineering machinery, Industry and Farm machines...  
Temperature for use : from -30°C / -22°F to +130°C / +266°F.

**PERFORMANCES**

**STANDARDS**                      DIN 51502 : KP 2 K-30

Multipurpose grease formulated with lithium soap, mineral base oil stock and with dedicated Extreme Pressure, anti-wear, anti-oxidation & anti-corrosion additivation.

Good adherence to metal.

Good resistance to load.

Resistant to water.

Good anti-corrosion and anti-rust protection.

Good mechanical stability.

**PROPERTIES**

Color	Visual	Brown
Consistency grade	DIN 51818	NLGI 2
Soap		Lithium
Penetrability - 60 cycles	ASTM D217	265 / 295 x10 <sup>-1</sup> mm
Drop point	ASTM D2265	180 °C / 356 °F
TIMKEN Test - Load	ASTM D2509	40.0 lb
Anti-corrosion EMCOR	IP 220	0 / 0
FAG FE-9 Test		

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty. Made in FRANCE

MOTUL - 119 Bd Félix Faure - 93303 - AUBERVILLIERS CEDEX - BP 94 - Tel: 33 1 48 11 70 00 - Fax: 33 1 48 33 28 79 - www.motul.com