



## MOTUL MULTIA SUPRA STOU 10W-30

Lubricant for engine, transmission & hydraulic system on agricultural and off-road equipment  
**STOU – Super Tractor Oil Universal Mineral**

### TYPE OF USE

**MULTIA SUPRA STOU 10W-30** is a high-quality mineral-based universal oil designed for use in tractors, combines, harvesters, and off-road equipment with or without turbocharged diesel engines. It lubricates the engine, transmission, hydraulic system, PTO (power take-off), final drive, and oil-immersed wet brakes.

**MULTIA SUPRA STOU 10W-30** is ZF TE-ML 06D approved for service fill on ZF Ecom 1.5 continuously variable transmissions fitted on Agtron TTV Same Deutz Fahr Group machinery.

Its universal nature simplifies maintenance, reduces the risk of using the wrong oil, minimizes stock requirements, and allows year-round use with optimal drain intervals.

This product is not suitable for diesel engines equipped with Diesel Particle Filters (DPF).

### PERFORMANCES

**MULTIA SUPRA STOU 10W-30** is formulated with highly refined solvent mineral base stocks and a specialized additive package that provides for

- excellent thermal and oxidation stability
- very low wet brake noise while limiting friction plate wear
- superior cold start performance
- strong protection against wear, corrosion, and foaming.

The soot control level of API CI-4 / ACEA E7 stands for outstanding dispersive properties to avoid oil filter plugging and to maintain engine cleanliness during the entire oil drain interval.

The SAE J300 viscosity grade 10W-30 corresponds to a SAE J306 75W-80.



## MOTUL MULTIA SUPRA STOU 10W-30

Lubricant for engine, transmission & hydraulic system on agricultural and off-road equipment  
STOU – Super Tractor Oil Universal  
Mineral

### RECOMMENDATIONS

Can be mixed with synthetic or mineral oils.

Oil changes should be performed according to the manufacturer's recommendations. Consult your vehicle's owner's manual or contact a dealer for specific guidelines, as they vary.

We also recommend the use of an oil monitoring program to optimize oil change intervals and maximize equipment protection.

### PROPERTIES

|                            |            |                       |
|----------------------------|------------|-----------------------|
| Color                      | ASTM D1500 | Amber                 |
| Viscosity grade            | SAE J 300  | 10W-30                |
| Density at 20°C (68°F)     | ASTM D1298 | 0.862                 |
| Viscosity at 40°C (104°F)  | ASTM D445  | 70 mm <sup>2</sup> /s |
| Viscosity at 100°C (212°F) | ASTM D445  | 11 mm <sup>2</sup> /s |
| Viscosity Index            | ASTM D2270 | 147                   |
| Pour point                 | ASTM D97   | -36 °C / -33 °F       |
| TBN                        | ASTM D2896 | 11 mg KOH/g           |
| Flash point                | ASTM D92   | 222 °C / 432 °F       |

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty.

MOTUL - 119 Bd Félix Faure - 93303 - Aubervilliers Cedex - BP 94 - FRANCE - Tel: 33 1 48 11 70 00 - Fax: 33 1 48 33 28 79 - [www.motul.com](http://www.motul.com)

Lubricant for engine, transmission & hydraulic system on agricultural and off-road equipment  
**STOU – Super Tractor Oil Universal Mineral**

| STANDARDS            |                                                             |
|----------------------|-------------------------------------------------------------|
| ACEA                 | E7                                                          |
| API                  | CF-4/SF, CI-4, GL-4                                         |
| ZF                   | TE-ML 06D                                                   |
| OEM PERFORMANCES     |                                                             |
| CASE IH              | MS-1118, MS-1207, MS-1209, MS-1210                          |
| CATERPILLAR          | TO-2                                                        |
| DAIMLER              | DTFR 15B110 (former MB 228.3) (level of piston cleanliness) |
| FORD                 | ESN-M2C134-D, ESN-M2C41-B, WSS-M2C121-E, WSS-M2C159-C       |
| JOHN DEERE           | JDM J20C, JDM J27                                           |
| MERCEDES-BENZ        | MB 227.1, MB 228.1 (engine performance in SAE 10W-30)       |
| NEW HOLLAND          | NH 024C, NH 324B, NH 410B, NH 540B                          |
| PRODUCTS             |                                                             |
| AGCO Massey-Ferguson | M1127, M1135, M1139, M1141, M1144, M1145                    |
| Allison              | C-4                                                         |
| Case New Holland     | MAT 3525                                                    |
| ZF                   | TE-ML 06B, TE-ML 06C, TE-ML 06R, TE-ML 07B                  |

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty.