



MOTUL MULTIA SUPRA UTTO 10W-30 EP

Lubricant for transmissions with wet brakes and hydraulic lift systems
UTTO – Universal Tractor Transmission Oil
Mineral

TYPE OF USE

MULTIA SUPRA UTTO 10W-30 EP specifically formulated for use in agricultural machinery transmissions equipped with wet brake systems and integrated hydraulic circuits. It is designed for multifunctional use in gearboxes, rear axles, hydraulic lifter systems, and wet brake assemblies.

This fluid is developed to serve multiple functions within agricultural machinery. It combines the properties of a gear oil and a hydraulic fluid, enabling it to lubricate transmissions, protect final drive components, operate hydraulic systems, and ensure smooth and quiet functioning of wet brakes – all from a single oil reservoir, streamlining lubricant inventories and simplifying stock management.

MULTIA SUPRA UTTO 10W-30 EP is suitable for a wide range of agricultural equipment, including machinery from major OEMs such as John Deere, Massey Ferguson, Case, SAME, International Harvester, New Holland, Ford, Fiat Agri, Renault, Claas, and other leading manufacturers.

PERFORMANCES

PERFORMANCES Massey-Ferguson M1135
 FORD ESN-M2C86-B

MULTIA SUPRA UTTO 10W-30 EP is specially formulated for tractor transmissions equipped with wet brakes operating under extreme conditions.

Its advanced additive technology ensures excellent Extreme Pressure (EP) performance, along with outstanding anti-oxidation, anti-corrosion, anti-wear, and anti-foam properties to ensure long-lasting protection and reliable operation across a wide range of agricultural applications.

RECOMMENDATIONS

Can be mixed with synthetic or mineral oils.



MOTUL MULTIA SUPRA UTTO 10W-30 EP

Lubricant for transmissions with wet brakes and hydraulic lift systems
UTTO – Universal Tractor Transmission Oil
Mineral

Oil changes should be performed according to the manufacturer's recommendations. Consult your vehicle's owner's manual or contact a dealer for specific guidelines, as they vary.

We also recommend the use of an oil monitoring program to optimize oil change intervals and maximize equipment protection.

PROPERTIES

Color	ASTM D1500	Amber
Viscosity grade	SAE J 300	10W-30
Density at 20°C (68°F)	ASTM D1298	0.884
Viscosity at 40°C (104°F)	ASTM D445	80.4 mm ² /s
Viscosity at 100°C (212°F)	ASTM D445	11.0 mm ² /s
Viscosity Index	ASTM D2270	125
Pour point	ASTM D97	-33.0 °C / -27.0 °F
Flash point	ASTM D92	246 °C / 475 °F

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty.

MOTUL - 119 Bd Félix Faure - 93303 - Aubervilliers Cedex - BP 94 - FRANCE - Tel: 33 1 48 11 70 00 - Fax: 33 1 48 33 28 79 - www.motul.com