

**NAUTIC GREASE**

**High Performance Multipurpose Marine Grease  
NLGI 2 - Extreme-Pressure  
Technosynthese® - Calcium**

**TYPE OF USE**

High performance multipurpose grease with Extreme Pressure properties, developed to lubricate and protect all mechanical parts against corrosion and wear in marine and humid environments.

To apply on parts in contact with water, sea water or under heavy loads and projections of sea spray: open gears, ball bearings or roller bearings, cables, chains, screws, hinges, etc...

**PERFORMANCES**

Technosynthese® grease using high performance synthetic base stock and Calcium soap with Extreme Pressure properties. NLGI 2 viscosity grade.

Temperature range: from -30°C / -22°F to +120°C / +248°F.

Advantages:

- Insoluble in water
- High level of adherence on surfaces.
- High anti-oxidation and anti-corrosion protection in salt water environments.
- High anti-wear, Extreme Pressure and thermal resistance properties
- High durability for less grease consumption

**PROPERTIES**

Color	Visual	Blue
Consistency grade	DIN 51818	NLGI 2
Soap		Calcium
Penetrability - 60 cycles	ASTM D217	265 / 295 x 10-1 mm
Drop point	ASTM D2265	150 °C / 302 °F
Water resistance	DIN 51807 T1	0 - 90
TIMKEN Test - Load	DIN 51434-03	55.0 lb
Anti-corrosion EMCOR	IP 220/85	0 / 0

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty. Made in FRANCE

MOTUL - 119 Bd Félix Faure - 93303 - AUBERVILLIERS CEDEX - BP 94 - Tel: 33 1 48 11 70 00 - Fax: 33 1 48 33 28 79 - www.motul.com