



## MOTUL NGEN HYBRID 0W-20



**Eco designed Fuel Economy motor oil - Gasoline engines  
Sustainable Synthetic blend**

### TYPE OF USE

Innovative and durable synthetic engine lubricant specially designed for Hybrid Electric Vehicles (H.E.V) and Plug-in Hybrid Electric Vehicles (P.H.E.V) fitted with recent gasoline engines, turbocharged or naturally aspirated, direct or indirect injection, designed to use SAE 0W-20 oil with low friction and low HTHS (High Temperature High Shear) viscosity ( $\geq 2.6$  mPa.s).

MOTUL NGEN HYBRID 0W-20 is especially formulated for the technical challenges imposed by Gasoline Hybrid cars, such as fuel dilution, water emulsion, high numbers of stop/start events and lower oil temperature conditions. This state-of-the-art formulation is part of a whole new Motul sustainable concept as it contains 25% of premium regenerated base oils and is filled in a 50% recycled and 100% recyclable Motul can, allowing Motul to lower its environmental footprint and favorise the circular economy.

MOTUL NGEN is the common naming to qualify the sustainable ranges at Motul using different technologies into the formulation and packaging to reduce its carbon footprint.

This dedicated formula can also be used for gasoline engines requiring a viscosity grade SAE 0W-20 lubricant or a "Fuel Economy" lubricant in viscosity grade 20, with API SP-RC, API SP and/or ILSAC GF-6A standards.

MOTUL NGEN HYBRID 0W-20 is suitable for Battery Electric Vehicles (B.E.V) fitted with thermal gasoline engine used as Range Extender.

Compatible with catalytic converters and particulate filters.

This type of oil may be unsuitable for use in some engines. Refer to the owner manual if in doubt.

### PERFORMANCES

STANDARDS	API SERVICE SP-RC ILSAC GF-6A
-----------	----------------------------------

RECOMMENDATIONS	HONDA, KIA, NISSAN, TOYOTA
-----------------	----------------------------

The API SP standard is fully backward compatible over API SN requirements and all former API standards. The API SP-RC "Resource Conserving" specification is even more demanding on the energy saving requirements.

API SP lubricants provide outstanding oxidation resistance, better anti-deposits protection, better engine cleanliness, anti-wear protection and enhanced performance at cold temperature for Fuel Economy savings during the whole oil life span.

Besides being backward compatible, compared to API SN and API SN Plus, the API SP standard provides higher performance and adds more protection against LSPI phenomenon for downsized direct injection turbocharged gasoline engines.

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty.



## MOTUL NGEN HYBRID 0W-20



**Eco designed Fuel Economy motor oil - Gasoline engines  
Sustainable Synthetic blend**

Based on the API SP specification, the ILSAC GF-6A standard for viscosity grade 20 lubricants is even more severe compared to ILSAC GF-5 especially on the Fuel Economy benefits performance. The requirements on the low viscosity "Fuel Economy" side of the lubricant, but also extended drain intervals, pistons/rings cleanliness, seals compatibility and reduced content of Phosphorus for enhancing after treatment systems compatibility. The ILSAC GF-6A specification also ensures perfect engine protection when gasoline containing up to 85% Ethanol is used (E85).

Viscosity grade SAE 0W-20 minimizes lubricant hydrodynamic friction, allows fuel economy benefits especially when the oil is cold.

This low viscosity grade also improves oil flow at start up, delivers faster oil pressure build up, faster rev raisings and allows to reach operating temperature faster, regardless of engine operating mode.

MOTUL NGEN HYBRID 0W-20 is specially formulated to meet the specific challenges of hybrid electric vehicles, such as HEV, PHEV and BEV with Range Extender, on which numerous and multiples unexpected stops and starts of the Gasoline engine are involved during the different operating phases of the hybrid vehicle. This particular mode of operation of the internal combustion engine on a hybrid vehicle generates very specific constraints for the lubricant such as fuel dilution, water emulsion, high numbers of stop/start events and lower oil temperature working conditions leading to increased oxidation, and for that purpose, MOTUL NGEN HYBRID 0W-20 fully meets all these demanding requirements.

Environmentally friendly, this type of oil allows fuel consumption reduction and therefore minimizes greenhouse gases (CO2) emissions.

### RECOMMENDATIONS

Drain interval: according to manufacturers' recommendations and tune to your own use.

MOTUL NGEN HYBRID 0W-20 can be mixed with synthetic or mineral oils.

Before use always refer to the owner manual of the vehicle.

### PROPERTIES

Viscosity grade	SAE J 300	0W-20
Density at 20°C (68°F)	ASTM D1298	0.843
Viscosity at 40°C (104°F)	ASTM D445	46.5 mm <sup>2</sup> /s
Viscosity at 100°C (212°F)	ASTM D445	8.6 mm <sup>2</sup> /s
HTHS viscosity at 150°C (302°F)	ASTM D4741	2.7 mPa.s

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty.



## MOTUL NGEN HYBRID 0W-20



**Eco designed Fuel Economy motor oil - Gasoline engines  
Sustainable Synthetic blend**

Viscosity Index	ASTM D2270	165.0
Pour point	ASTM D97	-48.0 °C / -54.0 °F
Sulfated Ash	ASTM D874	% weight 0.72
TBN	ASTM D2896	7.2 mg KOH/g
Flash point	ASTM D92	230.0 °C / 446.0 450 °F

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty.