



POWER LCV TURBO DIESEL

Technosynthese® Lubricant for Light Commercial Vehicle (LCV)
Technosynthese® Lubricant for Light Commercial Vehicle (LCV)
Technosynthese®

CONSEILS D'UTILISATIONS

POWER LCV TURBO DIESEL 10W40 is a Technosynthese® Lubricant for Light Commercial Vehicle (LCV).

PERFORMANCES

NORMES ACEA E7
API CI-4/CH-4

PERFORMANCES CUMMINS CES 20077, CUMMINS CES 20078, MERCEDES-BENZ MB-Approval 228.3, CASE IH JIC-501

POWER LCV TURBO DIESEL 10W40 is especially designed for GAZelle NEXT LCV with Cummins engines ISF 2.8 and ISF 3.8.

POWER LCV TURBO DIESEL 10W40 is also suitable for other generations of GAZ LCV (GAZelle BUSINESS...) and all low emissions Russian, European, American or Japanese Diesel engines naturally aspirated or Turbocharged, in line with Euro II, Euro III and Euro IV Application.

PROPRIÉTÉS

Grade de viscosité	SAE J 300	10W-40
Densité à 20°C		0.869
Viscosité à 40°C (104°F)	ASTM D445	102.0 mm²/s
Viscosité à 100°C (212°F)	ASTM D445	15.3 mm²/s
Indice de viscosité	ASTM D2270	158.0
Point d'écoulement	ASTM D97	-36.0 °C
TBN	ASTM D2896	10.1 mg KOH/g
Point éclair	ASTM D92	226.0 °C