



MOTUL POWERJET 10W-40 4T

**4 Stroke engine oil for Jet Ski
Technosynthese®**

TYPE OF USE

Specially designed for Jet Ski, Water Scooter, PWC – Personal Water Craft, Watercraft,... 4 Stroke marine engines, turbo-charged or supercharged. Leisure or racing use.

Compatible with catalytic converters.

Suitable for all type of petrol fuels, leaded or unleaded, with or without Ethanol, biofuels.

PERFORMANCES

The reinforced synthetic Technosynthese® base stock provides very high lubricating power which reduces frictions for higher power output and ensures resistance to very high temperatures reached in modern engines.

Outstanding detergent/dispersant properties avoiding sludge and deposits in the crankcase and maintaining engine cleanliness.

Protects against humid salt fog corrosion.

Anti-oxidation, Anti-wear, Anti-foam properties.

RECOMMENDATIONS

Drain interval: according to manufacturers' recommendations and tune to your own use.

Can be mixed with synthetic or mineral oils.

PROPERTIES

Viscosity grade	SAE J 300	10W-40
Density at 20°C (68°F)		0.870
Viscosity at 40°C (104°F)	ASTM D445	99.8 mm²/s
Viscosity at 100°C (212°F)	ASTM D445	14.9 mm²/s
Viscosity Index	ASTM D2270	152.0

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty.

MOTUL - 49 Kyalami Blvd, Kyalami Business Park - 1684 - Midrand - +27820454357 - www.motul.com

motul.com

09/25



MOTUL POWERJET 10W-40 4T

4 Stroke engine oil for Jet Ski
Technosynthese®

Pour point	ASTM D97	-36.0 °C / -33.0 °F
TBN	ASTM D2896	10.2 mg KOH/g
Flash point	ASTM D92	227.0 °C / 441.0 °F



MOTUL POWERJET 10W-40 4T

4 Stroke engine oil for Jet Ski
Technosynthese®

STANDARDS	
API	SM/SL

