



MOTUL RBF 660 FACTORY LINE

100% Synthetic Racing Brake Fluid – DOT 4
Very high boiling point: 325°C / 617°F
For hydraulic actuated brake and clutch systems

TYPE OF USE

For all types of hydraulically actuated brake and clutch systems requiring non-silicone synthetic fluid.
Specially designed to withstand the extreme temperature generated by racing carbon and ceramic brakes while allowing minimized air entrance for brake cooling.
Also suitable for conventional brakes with steel discs and for conventional hydraulic clutch actuators.
Exceeds DOT 3 and DOT 5.1 standards requirements, except for viscosity at -40°C / -40°F.

PERFORMANCES

Extreme thermal resistance and stability:

MOTUL RBF 660 FACTORY LINE very high dry boiling point (325°C / 617°F) exceeds the requirements of the standards DOT 5.1 non silicone base (260°C mini / 500°F mini) and DOT 4 (230°C mini / 446°F mini), and therefore enables effective braking even in extreme conditions.

Allows better aerodynamic performance by reducing the need for brake cooling air scoops on vehicles.

Efficient when rainy:

MOTUL RBF 660 FACTORY LINE very high wet boiling point (205°C / 401°F) is superior than the requirements of the standards DOT 5.1 non-silicone base (180°C mini / 356°F mini) and DOT 4 (155°C mini / 311°F mini), and therefore enables to keep efficient braking in wet conditions.

Indeed, DOT 3, DOT 4 or DOT 5.1 brake fluids have the property of absorbing moisture from the air, which reduces their boiling points and increases the risk of “vapor lock” phenomena.

The wet boiling point is measured after moistening the product with 3% water in order to be representative of the state of the fluid after 1 year of use.

RECOMMENDATIONS

Drain interval: always according to manufacturers' recommendations and to be tuned to your own use.

Avoid mixing with lower performance polyglycol-based brake fluids.

Do not mix with silicone (DOT 5 silicone base) or mineral base fluids (LHM).

Store brake fluid in its original container, tightly closed to prevent moisture absorption.

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty.

MOTUL - 49 Kyalami Blvd, Kyalami Business Park - 1684 - Midrand - +27820454357 - www.motul.com

motul.com

09/25



MOTUL RBF 660 FACTORY LINE

100% Synthetic Racing Brake Fluid – DOT 4
Very high boiling point: 325°C / 617°F
For hydraulic actuated brake and clutch systems

Aggressive chemical product if in contact with hands, paint or varnish.
If skin contact, rinse thoroughly with water.

PROPERTIES

Color	Visual	Amber
Viscosity at 100°C (212°F)		2.6 mm ² /s
Viscosity at -40°C (-40°F)		1,698.0 mm ² /s
Dry boiling point		325.0 °C / 617.0 °F
Wet boiling point		205.0 °C / 401.0 °F



MOTUL RBF 660 FACTORY LINE

100% Synthetic Racing Brake Fluid – DOT 4
Very high boiling point: 325°C / 617°F
For hydraulic actuated brake and clutch systems

STANDARDS	
FMVSS	116 DOT 4
SAE	J1703, J1704

