

**MOTUL****RBF 700 FACTORY LINE**

**100% Synthetic Racing Brake Fluid – DOT 4**  
**Very high boiling point: 336°C / 637°F**  
**For hydraulic actuated brake and clutch systems**

**USO**

MOTUL (Racing Brake Fluid) RBF 700 is a high-performance brake fluid developed to offer highly consistent and maximum braking power at extreme brake temperatures generated by carbon and ceramic racing brake discs systems.

Allows to minimize air vents of the brakes thus improving aerodynamic drag.

Can be used with conventional steel discs.

Can be used for clutch systems actuators.

RBF 700 meets DOT 4 standard allowing the fluid to be used in high performance vehicles for everyday use road applications.

**PRESTAÇÕES**

NORMAS FMVSS 116 DOT 4

**Extreme thermal resistance and stability:**

MOTUL RBF 700 FACTORY LINE very high dry boiling point (336°C / 637°F) is superior to all conventional brake fluids DOT 5.1 (260°C / 500°F mini) and DOT 4 (230°C / 446°F mini), and therefore enables effective braking in most extreme conditions.

Provides better aerodynamic performance by reducing air entrance for brake cooling.

**Efficient when rainy:**

MOTUL RBF 700 FACTORY LINE very high wet boiling point (205°C / 401°F) is superior to conventional brake fluids DOT 5.1 non-silicone base (180°C / 356°F mini) and DOT 4 (155°C / 311°F mini), and therefore enables to keep efficient braking in wet conditions.

Brake fluids tend to absorb humidity from the air which reduces boiling point and increase the risk of “vapor lock” phenomena or so called “spongy braking”.

The wet boiling point is measured by humidifying the product with 3% of water.



## RBF 700 FACTORY LINE

**100% Synthetic Racing Brake Fluid – DOT 4**  
**Very high boiling point: 336°C / 637°F**  
**For hydraulic actuated brake and clutch systems**

### RECOMENDAÇÕES

Avoid mixing with polyglycol based brake fluids.  
Do not mix with silicone (DOT 5 silicone base) or mineral base fluids (LHM).  
Store brake fluid in its original container and tightly closed to prevent moisture absorption.  
Aggressive chemical product if contact with hands, paint or varnish.  
If skin contact, rinse thoroughly with water.

### PROPIEDADS

Color	Visual	Âmbar
Viscosidade a 100°C (212°F)		2.1 mm <sup>2</sup> /s
Viscosidade a -40°C (-40°F)		1,580.0 mm <sup>2</sup> /s
Ponto de ebulição seco		336.0 ° C / 637.0 ° F
Ponto de ebulição húmido		205.0 ° C / 401.0 ° F