



MOTULTECH RUBRIC ARCTIC 26

High Performance Hydraulic Oil

DESCRIPTION

RUBRIC ARCTIC 26 is a high performance hydraulic fluid with a very high viscosity index for all year use in hydraulic equipment operating over a wide temperature range.

APPLICATIONS

High performance hydraulic fluid with a very high viscosity index for all year use in hydraulic equipment operating over a wide temperature range:

- (Outdoor) hydraulic systems operating under severe conditions cold start-up and high operating temperatures
- Hydrostatic transmissions and dashpots
- Shock absorbers and motor cycle front forks

ADVANTAGES

- Allows for very good start up performance of hydraulic equipment at very low temperatures
- Good rust and corrosion protection
- Very low pour point
- Zinc-free anti-wear additives for exceptional equipment performance
- Excellent oxidation stability
- Outstanding viscosity control over a wide temperature range



TECHNICAL INFORMATION

TECHNICAL CHARACTERISTICS	UNITS	METHOD	RUBRIC ARCTIC 26
Base oil	-		
Aspect	-		Clear
Color	-	ASTM D1500	1
Density	-	ISO 12185	0,871
Viscosity at 40°C	mm ² /s	ASTM D445	26.4
Viscosity at 100°C	mm ² /s	ASTM D445	8.2
Viscosity index	-	ASTM D2270	310.0
Flash point	°C	ASTM D92	242.0
Pour point	°C	ASTM D97	-56.0
Copper corrosion	-	NFT M 07105	1a
4 Ball test - Weld load	kg	ISO 20623	190
4 Ball test - Wear scar	mm	ASTM D4172	0,72

These characteristics are given only for information and can be updated over time.

SERVICES AND EQUIPMENT

In addition to its product ranges, MotulTech can provide tools and services for the maintenance and monitoring of your lubricants. Please contact your technical sales representative for more information.

Important Notice

All information and rules about health, safety and the environment are mentioned on the safety data sheet. It provides information about risks, safety procedures and first aid emergency rules. It clarifies all procedures to implement in the case of an accidental spillage, and for the disposal of the product and its effects on the environment. The safety data sheet is available on www.motul.com.

Our product contains natural additives which are likely to modify the colour of the concentrates without altering its performance. The specifications of our products are definite only at the time of order, and are subject to our general sale and guarantee conditions. To give our customers the latest technical developments, the general characteristics of our products may vary.