



RUBRIC CLEAN HM 32

HYDRAULIC SYSTEMS

DESCRIPTION

RUBRIC CLEAN HM 32 is a premium, anti-wear hydraulic oil specifically designed to prevent varnish from depositing on internal system components in hydraulic systems. **RUBRIC CLEAN HM** is the second part of a Hydraulic Clean Package that consists of the cleaner **RUBRIC R-CLEAN** and **RUBRIC CLEAN** hydraulic oils.

APPLICATIONS

In order to guarantee the best performance and a perfectly clean hydraulic system, **RUBRIC CLEAN HM 32** should only be used in either new or cleaned equipment.

The best way to prepare for the usage of **RUBRIC CLEAN** hydraulic oil is a treatment with the **RUBRIC R-CLEAN** hydraulic systems cleaner.

RUBRIC CLEAN HM 32 fulfils the most common specifications and OEM requirements:

- Parker Denison HF-0
- MAG IAS (ex Cincinnati Machine) P-68, P-69, P-70
- DIN 51524 part 1 (HL), 2 (HLP)
- Eaton Brochure 03-401-2010 (ex-Eaton Vickers M-2950-S / I-286-S)

ADVANTAGES

- Prevents the formation of varnish and sludge deposits.
- Keeps hydraulic components clean.
- Extended pump protection.
- Lowers maintenance and downtime costs.
- Provides excellent wear protection.
- Excellent oxidation and thermal stability.
- Protects metal surfaces from rust and corrosion.
- Excellent filtration properties.
- Maintains cycle times with clean equipment.
- Enables hydraulic systems to operate in their designed specification.

**TECHNICAL INFORMATION**

TECHNICAL CHARACTERISTICS	UNITS	METHOD	RUBRIC CLEAN HM 32
Base oil	-		
Aspect	-		Clear
Color	-	ASTM D1500	0.5
Density	-	ISO 12185	0,853
Viscosity at 40°C	mm ² /s	ASTM D445	31.5
Viscosity at 100°C	mm ² /s	ASTM D445	5.6
Viscosity index	-	ASTM D2270	117.0
Flash point	°C	ASTM D92	230.0
Pour point	°C	ASTM D97	-33.0
Copper corrosion	-	NFT M 07105	1a
4 Ball test - Weld load	kg	ISO 20623	160
4 Ball test - Wear scar	mm	ASTM D4172	0,49

These characteristics are given only for information and can be updated over time.

SERVICES AND EQUIPMENT

In addition to its product ranges, MotulTech can provide tools and services for the maintenance and monitoring of your lubricants. Please contact your technical sales representative for more information.



Important Notice

Information disclosed in this technical data sheet is based on MOTUL's experience and know-how in the development and manufacture of lubricants and other chemical products according to the current state of knowledge.

Any chemical product must be used in the intended application and in accordance with the recommendations provided in its safety data sheet freely consultable via the site <https://www.quickfds.com/fr/>. The performance of our products may be influenced by a series of factors, including conditions of use, application methods, operational environment, pretreatment of components, possible external contamination, etc ... For these reasons, universal recommendation of our products is impossible. The information in the technical data sheet represents general, non-binding guidelines and is given for guidance only. No express or implied warranty is given regarding the properties of the product or its suitability for a given application.

Therefore, we recommend consulting an application engineer to discuss application conditions and product performance criteria before use. It is the user's responsibility to test the functional suitability of the product and to use it under appropriate safety conditions. Our products are subject to continuous improvement with the aim of improving performance or bringing them into compliance with any new and possible regulations concerning them. We reserve the right to change our product lines, our products and their manufacturing processes and any provisions of our publications at any time without notice. This technical sheet cancels and replaces all previous editions.

We expressly draw the attention of any user to the fact that our product has not been designed and tested for use in the field of aeronautics as an "onboard" product or in the field of nuclear power production. Any use that may be made of the product in one of the aforementioned sectors will be under the exclusive responsibility of the user. Any reproduction, whatever its form, requires the prior written consent of MOTUL. All rights reserved.