



MOTULTECH RUBRIC EE 150

Hydraulic Fluids

DESCRIPTION

RUBRIC EE 150 is a hydraulic, circulating, slushing and anti-oxidation oils.

APPLICATIONS

RUBRIC EE 150 is an anti-corrosive and anti-oxidative hydraulic and circulating oil.

RUBRIC EE 150 meets the following requirements:

- ISO 11158 categories HL
- ISO 6743-4 category HL
- DIN 51524 part 1 HL
- NF E 48603 HL

ADVANTAGES

- Excellent resistance to oxidation.
- Excellent protection against corrosion.
- Good hydrolysis stability.
- Excellent desemulsification.
- Excellent thermal stability.

SERVICES AND EQUIPMENT

In addition to its product ranges, MotulTech can provide tools and services for the maintenance and monitoring of your lubricants. Please contact your technical sales representative for more information.

Important Notice

All information and rules about health, safety and the environment are mentioned on the safety data sheet. It provides information about risks, safety procedures and first aid emergency rules. It clarifies all procedures to implement in the case of an accidental spillage, and for the disposal of the product and its effects on the environment. The safety data sheet is available on www.motul.com.

Our product contains natural additives which are likely to modify the colour of the concentrates without altering its performance. The specifications of our products are definite only at the time of order, and are subject to our general sale and guarantee conditions. To give our customers the latest technical developments, the general characteristics of our products may vary.