



MOTULTECH RUBRIC HM 68

HYDRAULIC SYSTEMS
Hydraulic oil - Anti-wear
ISO VG 32 / 46 / 68 / 100
Mineral

TYPE OF USE

RUBRIC HM 68 is an anti-wear, anti-corrosion and anti-oxidation premium hydraulic oil adapted to the lubrication of hydraulic systems operating under severe conditions.

PERFORMANCES

RUBRIC HM 68 is recommended for use in all hydrodynamic power transmission machinery, hydraulic controls and hydrostatic systems widely used in all fields of technology such as transport, construction, mining as well as in machine tools, marine and aviation equipment.

PROPERTIES

Dielectric strength	ASTM D877	30.0
Color	Visual	Clear & bright
Viscosity grade	ISO	68
Density at 20°C (68°F)	ISO 12185	g/mL 0.88
Viscosity at 40°C (104°F)	ASTM D445	68.0 mm²/s
Viscosity at 100°C (212°F)	ASTM D445	8.6 mm²/s
Viscosity Index	ASTM D2270	104.0
Pour point	ASTM D97	-21.0 °C
Flash point	ASTM D92	≥ 225 °C

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty.

MOTUL - 49 Kyalami Blvd, Kyalami Business Park - 1684 - Midrand - +27820454357 - www.motul.com

motul.com



MOTULTECH RUBRIC HM 68

HYDRAULIC SYSTEMS
Hydraulic oil - Anti-wear
ISO VG 32 / 46 / 68 / 100
Mineral

STANDARDS	
AFNOR	NF E 48603 HM
DIN	51 524 part 2 HLP
ISO	11158 categories HM, 6743-4 categories HM
PRODUCTS	
Parker Denison	DENISON HF-0

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty.

MOTUL - 49 Kyalami Blvd, Kyalami Business Park - 1684 - Midrand - +27820454357 - www.motul.com

motul.com