

RUBRIC HV 22

Hydraulic Oil - High VI

MINERAL BASE**DESCRIPTION**

RUBRIC HV sont huiles hydrauliques à haut indice de viscosité, anti-usure, anti-corrosion et anti-oxydation. Hautes Performances adaptées à la lubrification des systèmes hydrauliques fonctionnant dans des conditions très sévères et sont soumis à de grandes différences de température.

BÉNÉFICES

- Excellent anti-wear quality
- Excellent resistance to oxidation
- Excellent protection against corrosion
- Good hydrolysis stability
- Excellent desemulsification
- Excellent thermal stability
- Excellent filterability
- High flash point

TECHNICAL INFORMATION

NAME	METHOD	RUBRIC HV 22
Couleur	Visuel	Ambre
Densité à 20°C (68°F)	ISO 12.185	0.859 kg/L
Viscosité à 40°C (104°F)	ASTM D445	22,0 mm ² /s
Viscosité à 100°C (212°F)	ASTM D445	4,7 mm ² /s
Index de viscosité	ASTM D2270	140,0
Point éclair	ASTM D92	204,0 °C
Point d'écoulement	ASTM D97	-45,0 °C

SERVICES AND EQUIPMENT

In addition to its product ranges, MotulTech can provide tools and services for the maintenance and monitoring of your lubricants. Please contact your technical sales representative for more information.

RECOMMENDATIONS

All information and rules about health, safety and the environment are mentioned on the safety data sheet. It provides information about risks, safety procedures and first aid emergency rules. It clarifies all procedures to implement in the case of an accidental spillage, and for the disposal of the product and its effects on the environment.

Our product contains natural additives which are likely to modify the colour of the concentrates without altering its performance. The specifications of our products are definite only at the time of order, and are subject to our general sale and guarantee conditions. To give our customers the latest technical developments, the general characteristics of our products may vary. The safety data sheet of this product is available at www.motul.com