



MOTUL RUBRIC HV 25

Synthetic Hydraulic Fluids

DESCRIPTION

RUBRIC HV 25 is a fully synthetic, ester based, anti-wear hydraulic fluid with a very high viscosity index.

APPLICATIONS

RUBRIC HV 25 is a specialty product suited for hydraulic systems and hydrostatic transmissions working in extreme conditions such as ultra-low and high temperatures, wide temperature range applications, high pressure.

ADVANTAGES

- Excellent oxidation and evaporation stability at high temperatures.
- Reinforced anti-wear performance.
- Excellent protection against corrosion.
- Low pour point and high viscosity index.
- Very good anti-foam properties.

SERVICES AND EQUIPMENT

In addition to its product ranges, MotulTech can provide tools and services for the maintenance and monitoring of your lubricants. Please contact your technical sales representative for more information.

Important Notice

All information and rules about health, safety and the environment are mentioned on the safety data sheet. It provides information about risks, safety procedures and first aid emergency rules. It clarifies all procedures to implement in the case of an accidental spillage, and for the disposal of the product and its effects on the environment. The safety data sheet is available on www.motul.com.

Our product contains natural additives which are likely to modify the colour of the concentrates without altering its performance. The specifications of our products are definite only at the time of order, and are subject to our general sale and guarantee conditions. To give our customers the latest technical developments, the general characteristics of our products may vary.