

RUBRIC HV 25

High Performance Hydraulic Fluid

SYNTHETIC BASE

DESCRIPTION

RUBRIC HV 25 is a high performance anti-wear hydraulic fluid with a very high viscosity index.

Recommended for all hydraulic systems, hydrostatic transmissions and dashpots subjected to wide temperature variations.

BÉNÉFICES

- Excellent oxidation and evaporation stability at high temperatures
- Reinforced anti-wear performance
- Excellent protection against corrosion
- Low pour point and high viscosity index
- Very good anti-foam properties

PERFORMANCES

RUBRIC HV 25 is a fully synthetic, ester based, anti-wear hydraulic fluid with a very high viscosity index.

RUBRIC HV 25 is a speciality product suited for hydraulic systems and hydrostatic transmissions working in extreme conditions such as ultra-low and high temperatures, wide temperature range applications, high pressure.

TECHNICAL INFORMATION

NAME	METHOD	RUBRIC HV 25
Couleur	Visuel	Clair
Densité à 20°C (68°F)	ISO 12.185	0.881 kg/L
Viscosité à 40°C (104°F)	ISO 3104	26,0 mm²/s
Viscosité à 100°C (212°F)	ISO 3104	8,6 mm²/s
Index de viscosité	ISO 2909	352,0
Point éclair	ISO 2592	100,0 °C
Point d'écoulement	ISO 3016	-63,0 °C
4 Ball test	ASTM D4172	0.68 mm Wear scar
Rust Test (Distilled Water/ Synthetic Sea Water)	ISO 7120 A	Pass
Rust Test (Distilled Water/ Synthetic Sea Water)	ISO 7120 B	Pass
Acid Number	ISO 6618	0,6

SERVICES AND EQUIPMENT

In addition to its product ranges, MotulTech can provide tools and services for the maintenance and monitoring of your lubricants. Please contact your technical sales representative for more information.

RECOMMENDATIONS

All information and rules about health, safety and the environment are mentioned on the safety data sheet. It provides information about risks, safety procedures and first aid emergency rules. It clarifies all procedures to implement in the case of an accidental spillage, and for the disposal of the product and its effects on the environment.

Our product contains natural additives which are likely to modify the colour of the concentrates without altering its performance. The specifications of our products are definite only at the time of order, and are subject to our general sale and guarantee conditions. To give our customers the latest technical developments, the general characteristics of our products may vary. The safety data sheet of this product is available at www.motul.com