

**MOTUL TECH
AMBIENT****RUBRIC****HV****46**

Hydraulic Fluid

MINERAL BASE

DESCRIPTION

RUBRIC HV 46 AMBIENT is a high performance anti-wear hydraulic oil, specifically designed to meet the needs of modern, high pressure, industrial and mobile equipment hydraulic systems.

APPLICATIONS

RUBRIC HV 46 AMBIENT is recommended for outdoor equipment which are likely to operate in wide temperature range, such as systems where cold start-up and high operating temperatures are typical (marine applications). It's suitable also for indoor manufacturing equipment that incorporates control systems requiring minimal viscosity change with temperature.

ADVANTAGES

- Suitable for applications operating in a wide temperature range thanks to high a viscosity index and an excellent viscosity stability.
- Suitable for hydraulic systems with very thin filters (3 microns).
- Very high thermal stability.
- Outstanding anti-wear properties.
- Helps to prevent aeration and cavitation damage thanks to rapid air release.
- Excellent demulsibility.
- Red coloured for easy leakage detection.



TECHNICAL INFORMATION

TECHNICAL CHARACTERISTICS	UNITS	METHOD	RUBRIC HV 46 AMBIENT
Color	-	Visual	Red
Density at 20°C (68°F)	-		0.870
Viscosity at 40°C (104°F)	mm ² /s	ASTM D445	46.0
Viscosity at 100°C (212°F)	mm ² /s	ASTM D445	8.0
Viscosity Index	-	ASTM D2270	146.0
Pour point	°C	ASTM D97	-42.0 / -33.0
4 Ball test - Wear scar	mm	ISO 20.623	0.47 (1h, 40kg)
Flash point	°C	ASTM D92	≥ 210

These characteristics are given only for information and can be updated over time.

SERVICES AND EQUIPMENT

In addition to its product ranges, MotulTech can provide tools and services for the maintenance and monitoring of your lubricants. Please contact your technical sales representative for more information.

Important Notice

Information disclosed in this technical data sheet is based on MOTUL's experience and know-how in the development and manufacture of lubricants and other chemical products according to the current state of knowledge.

Any chemical product must be used in the intended application and in accordance with the recommendations provided in its safety data sheet freely consultable via the site <https://www.quickfds.com/fr/>. The performance of our products may be influenced by a series of factors, including conditions of use, application methods, operational environment, pretreatment of components, possible external contamination, etc ... For these reasons, universal recommendation of our products is impossible. The information in the technical data sheet represents general, non-binding guidelines and is given for guidance only. No express or implied warranty is given regarding the properties of the product or its suitability for a given application.

Therefore, we recommend consulting an application engineer to discuss application conditions and product performance criteria before use. It is the user's responsibility to test the functional suitability of the product and to use it under appropriate safety conditions. Our products are subject to continuous improvement with the aim of improving performance or bringing them into compliance with any new and possible regulations concerning them. We reserve the right to change our product lines, our products and their manufacturing processes and any provisions of our publications at any time without notice. This technical sheet cancels and replaces all previous editions.

We expressly draw the attention of any user to the fact that our product has not been designed and tested for use in the field of aeronautics as an "onboard" product or in the field of nuclear power production. Any use that may be made of the product in one of the aforementioned sectors will be under the exclusive responsibility of the user. Any reproduction, whatever its form, requires the prior written consent of MOTUL. All rights reserved.