

## **RUBRIC LX 46**

Hydraulic Oil - Zinc-free

### MINERAL BASE

# DATA LUU ELUU SHU

#### DESCRIPTION

**RUBRIC LX** is an ash-free, high-performance, hydraulic oil suitable for the lubrication of hydraulic systems operating in severe conditions.

#### BÉNÉFICES

- Excellent anti-wear properties
- Excellent oxidation resistance
- Excellent corrosion protection
- Good hydrolysis stability
- Excellent demulsion
- Excellent thermal stability

#### **PERFORMANCES**

**RUBRIC LX** are suitable for a wide range of hydraulic power applications found in manufacturing and industrial environments.

They are especially suitable for machine tool applications where a zinc-free hydraulic fluid is recommended by the machine manufacturer or where the hydraulic oil can contaminate metalworking fluids.

#### TECHNICAL INFORMATION

NAME	METHOD	RUBRIC LX 46
Couleur	Visuel	Clair
Densité à 20°C (68°F)	ISO 12.185	0.872 kg/L
Viscosité à 40°C (104°F)	ASTM D445	46,0 mm²/s
Viscosité à 100°C (212°F)	ASTM D445	6,9 mm²/s
Index de viscosité	ASTM D2270	109,0
Point éclair	ASTM D92	238,0 °C
Point d'écoulement	ASTM D97	-27,0 °C

MOTUL | www.motul.fr 33 1 48 11 70 00 | tech@motul.fr Creation Date: 01/2018 Revision Date: 07/2018



## DATA L U U I

Creation Date: 01/2018

Revision Date: 07/2018

#### SERVICES AND EQUIPMENT

In addition to its product ranges, MotulTech can provide tools and services for the maintenance and monitoring of your lubricants. Please contact your technical sales representative for more information.

#### RECOMMENDATIONS

All information and rules about health, safety and the environment are mentioned on the safety data sheet. It provides information about risks, safety procedures and first aid emergency rules. It clarifies all procedures to implement in the case of an accidental spillage, and for the disposal of the product and its effects on the environment.

Our product contains natural additives which are likely to modify the colour of the concentrates without altering its performance. The specifications of our products are definite only at the time of order, and are subject to our general sale and guarantee conditions. To give our customers the latest technical developments, the general characteristics of our products may vary. The safety data sheet of this product is available at www.motul.com