

**SAE 10W-40****Gasoline and Diesel engine oil  
Technosynthese®****TYPE OF USE**

Designed for the old generation of Gasoline and Diesel engines.  
Suitable for all type of fuels: leaded or unleaded Gasoline, LPG, CNG, Diesel and Biofuels.  
Compatible for catalytic converters.  
All driving conditions: City, Road, Highway.

**PERFORMANCES****STANDARDS** API SL / CF

The SAE 10W-40 viscosity grade facilitates cold starts and fits most recent Gasoline and Diesel engines.  
The reinforced Technosynthese® synthetic formulation limits volatility and provides high lubricity in order to reduce friction and withstand high temperatures.  
Detergent and dispersing agents to keep the engine clean.  
Efficient anti-wear additivation to increase engine lifetime.  
Anti-oxidation properties.  
Anti-corrosion, Anti-foam properties.

**RECOMMENDATIONS**

Drain interval: according to manufacturers' requirements and to be adjusted according to your own use.  
MOTUL SAE 10W-40 can be mixed with synthetic or mineral oils.

**PROPERTIES**

Viscosity grade	SAE J 300	10W-40
Density at 20°C (68°F)	ASTM D1298	0.866
Viscosity at 40°C (104°F)	ASTM D445	93.5 mm <sup>2</sup> /s

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty. Made in FRANCE

MOTUL - 119 Bd Félix Faure - 93303 - AUBERVILLIERS CEDEX - BP 94 - Tel: 33 1 48 11 70 00 - Fax: 33 1 48 33 28 79 - www.motul.com



**SAE 10W-40**

**Gasoline and Diesel engine oil  
Technosynthese®**

Viscosity at 100°C (212°F)	ASTM D445	13.7 mm <sup>2</sup> /s
Viscosity Index	ASTM D2270	149.0
Pour point	ASTM D97	-33.0 °C / -27.4 °F
Flash point	ASTM D92	230.0 °C / 446.0 °F
TBN	ASTM D2896	6.1 mg KOH/g