

## SAFCO RUBRIC AW22

Premium Hydraulic and Circulating Oil

### MINERAL BASE

#### DESCRIPTION

**RUBRIC AW 22** is a hydraulic, circulating, slushing and anti-oxidation oil.

#### BÉNÉFICES

- Excellent anti-wear properties
- Anti-oxidation and anti-corrosion properties
- Excellent anti-foam properties
- Very good stability against hydrolysis
- High thermal stability
- Extended equipments life

#### TECHNICAL INFORMATION

NAME	METHOD	SAFCO RUBRIC AW22
Densité à 20°C (68°F)	ISO 12.185	0.863 kg/L
Viscosité à 40°C (104°F)	ASTM D445	22,0 mm <sup>2</sup> /s
Viscosité à 100°C (212°F)	ASTM D445	4,1 mm <sup>2</sup> /s
Index de viscosité	ASTM D2270	98,0
Point éclair	ASTM D92	211,0 °C
Point d'écoulement	ASTM D97	-30,0 °C

#### SERVICES AND EQUIPMENT

In addition to its product ranges, MotulTech can provide tools and services for the maintenance and monitoring of your lubricants. Please contact your technical sales representative for more information.

**RECOMMENDATIONS**

All information and rules about health, safety and the environment are mentioned on the safety data sheet. It provides information about risks, safety procedures and first aid emergency rules. It clarifies all procedures to implement in the case of an accidental spillage, and for the disposal of the product and its effects on the environment.

Our product contains natural additives which are likely to modify the colour of the concentrates without altering its performance. The specifications of our products are definite only at the time of order, and are subject to our general sale and guarantee conditions. To give our customers the latest technical developments, the general characteristics of our products may vary. The safety data sheet of this product is available at [www.motul.com](http://www.motul.com)