

SAFCO RUBRIC B46

Premium Hydraulic and Circulating Oil

MINERAL BASE

DESCRIPTION

Anti-corrosive and anti-oxidative hydraulic and circulating oil.

BÉNÉFICES

- Excellent anti-wear properties
- Anti-oxidation and anti-corrosion properties
- Excellent anti-foam properties
- Excellent anti-wear properties
- High thermal stability
- Higher system efficiency, less service down-time
- Extended equipments life

TECHNICAL INFORMATION

NAME	METHOD	SAFCO RUBRIC B46
Viscosité à 40°C (104°F)		46,0 mm ² /s
Viscosité à 100°C (212°F)		6,8 mm ² /s
Index de viscosité		102,0
Point éclair		242,0 °C
Point d'écoulement		-27,0 °C

SERVICES AND EQUIPMENT

In addition to its product ranges, MotulTech can provide tools and services for the maintenance and monitoring of your lubricants. Please contact your technical sales representative for more information.

RECOMMENDATIONS

All information and rules about health, safety and the environment are mentioned on the safety data sheet. It provides information about risks, safety procedures and first aid emergency rules. It clarifies all procedures to implement in the case of an accidental spillage, and for the disposal of the product and its effects on the environment.

Our product contains natural additives which are likely to modify the colour of the concentrates without altering its performance. The specifications of our products are definite only at the time of order, and are subject to our general sale and guarantee conditions. To give our customers the latest technical developments, the general characteristics of our products may vary. The safety data sheet of this product is available at www.motul.com