

SAFCO RUBRIC BIO 46

Biodegradable Hydraulic Oil

100% SYNTHETIC BASE

DESCRIPTION

High performance hydraulic fluid based on synthetic esters with a high level of biodegradability (> 90 % in 21 days). Recommended for all hydraulic systems. **RUBRIC BIO** has the European Ecolabel and the Blue Angel approval and meets the Bosch Rexroth RE 90221-01 specification.

BENEFITS

- Excellent thermal stability
- Excellent anti-wear performance and oxidation resistance
- Good filterability
- Excellent desémulsion
- High viscosity index

TECHNICAL INFORMATION

NAME	METHOD	SAFCO RUBRIC BIO 46
Viscosity at 40°C (104°F)	ASTM D445	49.5 mm²/s
Viscosity at 100°C (212°F)	ASTM D445	9.8 mm²/s
Viscosity Index	ASTM D2270	186.0
Flash point	ASTM D92	>310 °C
Pour point	ASTM D97	-30.0 °C

SERVICES AND EQUIPMENT

In addition to its product ranges, MotulTech can provide tools and services for the maintenance and monitoring of your lubricants. Please contact your technical sales representative for more information.

RECOMMENDATIONS

All information and rules about health, safety and the environment are mentioned on the safety data sheet. It provides information about risks, safety procedures and first aid emergency rules. It clarifies all procedures to implement in the case of an accidental spillage, and for the disposal of the product and its effects on the environment.

Our product contains natural additives which are likely to modify the colour of the concentrates without altering its performance. The specifications of our products are definite only at the time of order, and are subject to our general sale and guarantee conditions. To give our customers the latest technical developments, the general characteristics of our products may vary. The safety data sheet of this product is available at www.motul.com