

MOTULTECH SAFKLEEN 234

Degreasing Agent

DESCRIPTION

SAFKLEEN 234 is a water-based cleaner that can be used, either by spraying or by ultrasonic immersion, for the degreasing and the temporary passivation of all types of metals.

SAFKLEEN 234 can be used in spraying washing machines where perfect cleaning is required after heat treatment of steel and when a low VOC content product is needed (below 10%).

SAFKLEEN 234 exerts its detergent action in a concentration range from 1 to 5% and in a temperature range from 30°C to 60°C, maintaining a controlled level of foam.

APPLICATIONS

SAFKLEEN 234 can be used in spraying washing machines where perfect cleaning is required after heat treatment of steel and when a low VOC content product is needed (below 10%).

SAFKLEEN 234 exerts its detergent action in a concentration range from 1 to 5% and in a temperature range from 30°C to 60°C, maintaining a controlled level of foam.

ADVANTAGES

- Corrosion protection.
- Easy to rinse.
- Low foaming.
- Can be used with any type of water.
- Boron and phosphate free.
- Very good biostability.

TECHNICAL INFORMATION

TECHNICAL CHARACTERISTICS	UNITS	METHOD	SAFKLEEN 234
pH	-	NFT 60.193	10.5 (ph Pure)
Break Point Corrosion	%	IP 287	3
Refractometer Factor	-		3.1

These characteristics are given only for information and can be updated over time.

SERVICES AND EQUIPMENT

In addition to its product ranges, MotulTech can provide tools and services for the maintenance and monitoring of your lubricants. Please contact your technical sales representative for more information.