



MOTULTECH SAFKLEEN 334

METAL PARTS DEGREASER

AQUEOUS FLUID

DESCRIPTION

SAFKLEEN 334 is a caustic free water-based cleaner used for degreasing by spraying on aluminum, iron, cast iron, zinc, copper and its alloys, contaminated by grease and mineral oils.

APPLICATIONS

SAFKLEEN 334 is generally used where in addition to a degreasing treatment is also required anti-oxidant protection of the metal parts.

SAFKLEEN 334 allows mineral oils and greases elimination.

SAFKLEEN 334 can be used by spraying up to 5 bars, by dipping or by ultrasonic in a temperature range from 30°C to 50°C.

ADVANTAGES

- Protection against oxidation.
- Easy to rinse.
- Fully organic.
- Use at low temperature.
- Can be used with any type of water.
- Boron and phosphate free.
- Very good bio-stability.

TECHNICAL INFORMATION

TECHNICAL CHARACTERISTICS	UNITS	METHOD	SAFKLEEN 334
Aspect	-		Clear / Light Yellow
pH	-	NFT 60.193	8.9 (5% in water)
Break Point Corrosion	%	IP 287	> 10
Refractometer Factor	-		3.0
Storage	-		in frost-free, dry place

These characteristics are given only for information and can be updated over time.

RECOMMENDED CONCENTRATIONS OF USE

- Aluminium and zinc: 1-4%
- Ferrous metals: 5-15%

HEALTH AND SAFETY

- Free from chlorinated additives and boron



- Phosphate free
- Good dermatological behavior for better user comfort

SERVICES AND EQUIPMENT

In addition to its product ranges, MotulTech can provide tools and services for the maintenance and monitoring of your lubricants. Please contact your technical sales representative for more information.

Important Notice

All information and rules about health, safety and the environment are mentioned on the safety data sheet. It provides information about risks, safety procedures and first aid emergency rules. It clarifies all procedures to implement in the case of an accidental spillage, and for the disposal of the product and its effects on the environment. The safety data sheet is available on www.motul.com.

Our product contains natural additives which are likely to modify the colour of the concentrates without altering its performance. The specifications of our products are definite only at the time of order, and are subject to our general sale and guarantee conditions. To give our customers the latest technical developments, the general characteristics of our products may vary.