



SAFKOOL 6220

METALWORKING FLUID FOR CUTTING AND GRINDING

SEMI-SYNTHETIC BASE

DESCRIPTION

SAFKOOL 6220 is a water emulsifiable metalworking fluid concentrate dedicated for general purpose machining operations that require high cooling properties. The product is recommended for the grinding and machining of ferrous and non-ferrous alloys, including standard aluminum alloys and yellow metals. The product provides good cost savings as well as machining excellence for shofloor operations. The product is suitable for hard and very hard water conditions.

APPLICATIONS

SAFKOOL 6220 is a semi-synthetic water soluble oil, which is free from formaldehyde release agents. The product can be used for machining and grinding applications for alloy steel and cast iron, standard aluminium metallurgiques as well as yellow metals. The unique additive base prevents premature discoloration of the emulsion with yellow metals. The product provides good anti corrosion properties with stable pH. The product can be used for machining operations of yellow metals. However, we recommend to check the tendency of the alloy to stain before use.

ADVANTAGES

- Excellent lubricating and cooling properties.
- Optimization of surface finish and endurance.
- Excellent bio stability and stability in use.
- Operator friendly.
- Cleanliness of working environment.

TECHNICAL INFORMATION

| TECHNICAL CHARACTERISTICS | UNITS | METHOD | SAFKOOL 6220 |
|---------------------------|-------|------------|--------------|
| Color | - | | Yellow |
| Density | - | ASTM D4052 | 1.022 |
| pH | - | NFT 60.193 | 9.4 at 5 % |
| Break Point Corrosion | % | IP 287 | 3.5 |
| Refractometer Factor | - | | 1.6 |
| Water Hardness range | ppm | | 200-800 |

These characteristics are given only for information and can be updated over time.



RECOMMENDED CONCENTRATIONS OF USE

- General machining of iron and steel: 4-6 %
- General machining of aluminium: 6-8 %
- Machining of copper alloys: 4-6 %
- Heavy duty machining: 8-15 %

HEALTH AND SAFETY

- Bactericide, formaldehydes and formaldehydes releasers free
- Nitrites, glycol ether and DEA free, without chlorinated or sulfur additives
- Operator friendly : Good dermatological behavior and easy to use

The refractometer reading must be multiplied by the refractometer factor to arrive at the real concentration.

INSTRUCTIONS

Before first fill, thoroughly clean the installation with an antiseptic such as **Contram CB3**. Drain and rinse the system with water.

If no volumetric mixing system is available, slowly pour **SAFKOOL 6220** into water while stirring continuously to achieve a correct preparation of the emulsion. To ensure the best quality of emulsion and maximize the fluid efficiency, consult the **Good Practices Handbook - Metalworking Soluble Fluids**.

Storage Conditions :

The product should be stored between 5°C and 40°C for best performance. The product should be stored away from direct sunlight and in a cool, covered and dry area.

SERVICES AND EQUIPMENT

In addition to its product ranges, MotulTech can provide tools and services for the maintenance and monitoring of your lubricants. Please contact your technical sales representative for more information.



Important Notice

Information disclosed in this technical data sheet is based on MOTUL's experience and know-how in the development and manufacture of lubricants and other chemical products according to the current state of knowledge.

Any chemical product must be used in the intended application and in accordance with the recommendations provided in its safety data sheet freely consultable via the site <https://www.quickfds.com/fr/>. The performance of our products may be influenced by a series of factors, including conditions of use, application methods, operational environment, pretreatment of components, possible external contamination, etc ... For these reasons, universal recommendation of our products is impossible. The information in the technical data sheet represents general, non-binding guidelines and is given for guidance only. No express or implied warranty is given regarding the properties of the product or its suitability for a given application.

Therefore, we recommend consulting an application engineer to discuss application conditions and product performance criteria before use. It is the user's responsibility to test the functional suitability of the product and to use it under appropriate safety conditions. Our products are subject to continuous improvement with the aim of improving performance or bringing them into compliance with any new and possible regulations concerning them. We reserve the right to change our product lines, our products and their manufacturing processes and any provisions of our publications at any time without notice. This technical sheet cancels and replaces all previous editions.

We expressly draw the attention of any user to the fact that our product has not been designed and tested for use in the field of aeronautics as an "onboard" product or in the field of nuclear power production. Any use that may be made of the product in one of the aforementioned sectors will be under the exclusive responsibility of the user. Any reproduction, whatever its form, requires the prior written consent of MOTUL. All rights reserved.