

**4-stroke motor oil, Scooters and Maxi Scooters
Urban riding & Commuting
100% Synthetic – JASO MB – Low Emissions**

TYPE OF USE

MOTUL Scooter Power 4T MB 10W-30 is a 100% synthetic 4-stroke motor oil for Scooters and Maxi Scooters without wet clutch.

It is specially designed for 4-stroke scooter engines of any displacement, with or without catalytic converter and is suitable for all type of leaded or unleaded gasoline fuels as well as biofuels.

PERFORMANCES

STANDARDS API SP

PERFORMANCES JALOS MB No. M033MOT229

Features and benefits

- 100% synthetic lubricant with an innovative package of anti-wear additives to reduce internal friction and thus improve mechanical efficiency.
 - Special formula for maximum efficiency and protection, instant engine response and optimized fuel economy.
 - Improved oil film resistance for excellent protection at high temperatures and therefore particularly suitable for use in urban traffic: full load over long periods and stop & go operation with difficult engine cooling conditions.
 - The API SP standard guarantees performance benefits including emissions system compatibility, oxidative stability and deposit control for the most severe modern hardware applications.
 - The JASO MB specification ensures optimum engine performance and fuel economy. Compared to a JASO MA lubricant, this JASO MB lubricant offers real energy savings: Up to 2.5 % less fuel consumption compared to a 20W-50 JASO MA lubricant and up to 2 % savings compared to a 10W-40 JASO MA oil, under same urban driving conditions and in start-stop operation.
- By reducing fuel consumption, this JASO MB lubricant contributes to a reduction in pollutant and thus CO2 emissions.

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty.



SCOOTER POWER MB 4T 10W-30

**4-stroke motor oil, Scooters and Maxi Scooters
Urban riding & Commuting
100% Synthetic – JASO MB – Low Emissions**

RECOMMENDATIONS

Drain interval: Up to 8,000 km, depending on manufacturer's recommendations or individual use.
Can be mixed with synthetic or mineral lubricants.

PROPERTIES

Viscosity grade	SAE J 300	10W-30
Density at 20°C (68°F)	ASTM D1298	0.852
Viscosity at 40°C (104°F)	ASTM D445	69.8 mm ² /s
Viscosity at 100°C (212°F)	ASTM D445	10.8 mm ² /s
Viscosity Index	ASTM D2270	144.0
Pour point	ASTM D97	-33.0 °C / -27.0 °F
TBN	ASTM D2896	7.1 mg KOH/g
Flash point	ASTM D92	256.0 °C / 493.0 °F

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty.