



SLID FILM 68

SLIDEWAY LUBRICATION

MINERAL OIL

DESCRIPTION

SLID FILM 68 is a premium oil for the lubrication of machine tool slides, centralised heating oil systems and machine tool hydraulic systems.

APPLICATIONS

SLID FILM 68 is a high performances lubricating oil for slideways, hydraulic and centralized lubrication systems.

SLID FILM 68 meets various international standards for slideways, hydraulic and gear lubrication:

SLIDEWAYS

ISO 11158 category HG

ISO 6743-4 category HG

ISO 6743-13 category G

CINCINNATI MILACRON P-47 and P-50

HYDRAULICS

ISO 11158 category HM

ISO 6743-4 category HM

DIN 51524 part 2

GEARS

US STEEL 224

DIN 51517 part 3

AGMA 9005 - E02

ADVANTAGES

- High demulsification properties with soluble cutting fluids.
- Resistance to corrosion.
- Excellent adhesion.
- Anti-wear and extreme-pressure.
- Suitable for lubrication of coated slides (SKC).
- Low frictional sliding coefficient.
- Prevents Stick-Slip.

**TECHNICAL INFORMATION**

TECHNICAL CHARACTERISTICS	UNITS	METHOD	SLID FILM 68
Base oil	-		
Aspect	-		Clear
Color	-	Visual	Amber
Density	-	ISO 12185	0,876
Viscosity at 40°C	mm ² /s	ISO 3104	71.6
Viscosity at 100°C	mm ² /s	ISO 3104	9.3
Viscosity index	-	ASTM D2270	106.0
Flash point	°C	ASTM D92	242.0
Pour point	°C	ASTM D97	-24.0
Copper corrosion	-	ASTM D130	1b
4 Ball test - Weld load	kg	ISO 20623	200
4 Ball test - Wear scar	mm	ISO 20623	0,4

These characteristics are given only for information and can be updated over time.

SERVICES AND EQUIPMENT

In addition to its product ranges, MotulTech can provide tools and services for the maintenance and monitoring of your lubricants. Please contact your technical sales representative for more information.



Important Notice

Information disclosed in this technical data sheet is based on MOTUL's experience and know-how in the development and manufacture of lubricants and other chemical products according to the current state of knowledge.

Any chemical product must be used in the intended application and in accordance with the recommendations provided in its safety data sheet freely consultable via the site <https://www.quickfds.com/fr/>. The performance of our products may be influenced by a series of factors, including conditions of use, application methods, operational environment, pretreatment of components, possible external contamination, etc ... For these reasons, universal recommendation of our products is impossible. The information in the technical data sheet represents general, non-binding guidelines and is given for guidance only. No express or implied warranty is given regarding the properties of the product or its suitability for a given application.

Therefore, we recommend consulting an application engineer to discuss application conditions and product performance criteria before use. It is the user's responsibility to test the functional suitability of the product and to use it under appropriate safety conditions. Our products are subject to continuous improvement with the aim of improving performance or bringing them into compliance with any new and possible regulations concerning them. We reserve the right to change our product lines, our products and their manufacturing processes and any provisions of our publications at any time without notice. This technical sheet cancels and replaces all previous editions.

We expressly draw the attention of any user to the fact that our product has not been designed and tested for use in the field of aeronautics as an "onboard" product or in the field of nuclear power production. Any use that may be made of the product in one of the aforementioned sectors will be under the exclusive responsibility of the user. Any reproduction, whatever its form, requires the prior written consent of MOTUL. All rights reserved.