

## SLIDFILM 68

Slideway Oil

## MINERAL BASE

### DESCRIPTION

**SLIDFILM** are premium oils for the lubrication of machine tool slides, centralised heating oil systems and machine tool hydraulic systems.

### BÉNÉFICES

- High demulsification properties with soluble cutting fluids
- Resistance to corrosion
- Excellent adhesion
- Anti-wear and extreme-pressure
- Suitable for lubrication of coated slides (SKC)
- Low frictional sliding coefficient
- Prevents Stick-Slip

### PERFORMANCES

Suitable for slideways, hydraulic and centralised lubrication systems.  
Meets various international standards for slideways, hydraulic and gear lubrication.

### TECHNICAL INFORMATION

NAME	METHOD	SLIDFILM 68
Densité à 20°C (68°F)	ISO 3675	0.876 kg/L
Viscosité à 40°C (104°F)	ISO 3104	68,0 mm²/s
Viscosité à 100°C (212°F)	ISO 3104	9,0 mm²/s
Point éclair	ISO 2592	238,0 °C
Point d'écoulement	ISO 3016	-27,0 °C

## SERVICES AND EQUIPMENT

In addition to its product ranges, MotulTech can provide tools and services for the maintenance and monitoring of your lubricants. Please contact your technical sales representative for more information.

## RECOMMENDATIONS

All information and rules about health, safety and the environment are mentioned on the safety data sheet. It provides information about risks, safety procedures and first aid emergency rules. It clarifies all procedures to implement in the case of an accidental spillage, and for the disposal of the product and its effects on the environment.

Our product contains natural additives which are likely to modify the colour of the concentrates without altering its performance. The specifications of our products are definite only at the time of order, and are subject to our general sale and guarantee conditions. To give our customers the latest technical developments, the general characteristics of our products may vary. The safety data sheet of this product is available at [www.motul.com](http://www.motul.com)