

SNOWPOWER 2T EST

2 stroke engine lubricant for Snowmobile Technosynthese® - Ester

TYPE OF USE

Specially formulated for snowmobile with 2 Stroke engines working under the most extreme weather conditions: polar cold. All snowmobile 2 stroke engines with injector systems or lubricated by premix.

All type of use including racing.

PERFORMANCES

STANDARDS API TC

ISO -L-EGD

PERFORMANCES JALOS JASO FD under N° 033MOT068

Synthetic lubricant Technosynthese® - Ester based with low pour point (-45°C / -49°F) formulated with a low content of solvent for easy start up at very low temperature.

Low ash formulation lubricant, Ester based with an effective detergent & dispersant power for a perfect piston, chamber and power valves cleanliness.

Mixes instantaneously with gasoline and remains stable.

Reduces friction and wear to increase engine life.

Anti-smoke.

RECOMMENDATIONS

Mixing ratio: from 2% to 4% (from 50:1 to 25:1) according to manufacturers' requirements and adjust according to your own

PROPERTIES

Color Visual Blue

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development. br\>
Product specifications are definitive from the order which is subject to our general conditions of sale and warranty. Made in FRANCE
MOTUL - 119 Bd Félix Faure - 93303 - Aubervilliers Cedex - BP 94 - Tel: 33 1 48 11 70 00 - Fax: 33 1 48 33 28 79 - www.motul.com



SNOWPOWER 2T EST

2 stroke engine lubricant for Snowmobile Technosynthese® - Ester

Density at 20°C (68°F)	ASTM D1298	0.856
Viscosity at 40°C (104°F)	ASTM D445	43.1 mm ² /s
Viscosity at 100°C (212°F)	ASTM D445	7.0 mm ² /s
Viscosity Index	ASTM D2270	123.0
Flash point	ASTM D92	146.0 °C / 295.0 °F
Pour point	ASTM D97	-45.0 °C / -49.0 °F
TBN	ASTM D2896	2.0 mg KOH/g