

**2-Stroke Engine Lubricant for Snowmobile
Premix or injector systems
100% Synthetic - Ester**

TYPE OF USE

SnowPower Synth 2T is a 100% synthetic ester-based high-performance lubricant, specially formulated for 2-stroke snowmobile engines operating in extreme cold and harsh winter conditions.

This lubricant is suitable for all 2-stroke snowmobile engines, whether indirect or direct fuel injection, and compatible with both oil injection systems and premix lubrication.

Designed for all types of use, including competitive racing.

PERFORMANCES

STANDARDS

API TC

ISO -L-EGD

JASO FD (under N° 033MOT080)

100% synthetic, ester-based lubricant with a low pour point (-57°C / -71°F), specifically formulated with minimal solvent content to ensure reliable cold starts in extremely low temperatures and harsh climates.

- **Low-ash formulation** with strong detergent and dispersant properties to maintain exceptional cleanliness of pistons, combustion chambers, and power valves.
- **Ester technology** minimizes deposits, enhances combustion efficiency, and delivers maximum performance at high RPM.
- **Instantly mixes with gasoline and remains stable**, ensuring consistent lubrication.
- **Reduces friction and wear**, extending engine life.
- **Anti-smoke formulation** for cleaner exhaust emissions.

RECOMMENDATIONS

Mixing ratio: 2% to 4% (50:1 to 25:1) according to manufacturer specifications. Adjust the ratio based on your specific use and operating conditions.

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty.

MOTUL - 119 Bd Félix Faure - 93303 - Aubervilliers Cedex - BP 94 - FRANCE - Tel: 33 1 48 11 70 00 - Fax: 33 1 48 33 28 79 - www.motul.com

motul.com



MOTUL SNOWPOWER SYNTH 2T

2-Stroke Engine Lubricant for Snowmobile
Premix or injector systems
100% Synthetic - Ester

PROPERTIES

Color	Visual	Green
Density at 20°C (68°F)	ASTM D1298	0.869
Viscosity at 40°C (104°F)	ASTM D445	70 mm ² /s
Viscosity at 100°C (212°F)	ASTM D445	11 mm ² /s
Viscosity Index	ASTM D2270	153
Pour point	ASTM D97	-59 °C / -74 °F
TBN	ASTM D2896	2 mg KOH/g
Flash point	ASTM D92	152 °C / 306 °F