

SOFT GREASE 0

Soft grease for gear cases
Lithium
NLGI 0 – Extreme Pressure

TYPE OF USE

Soft grease for lubrication of reduction gears or central lubrication systems, depending on manufacturers' recommendation.
 Civil engineering machinery, Agriculture, Industry.
 Temperatures for use : from -40°C / -40°F to +120°C / +248°F.

PERFORMANCES

STANDARDS DIN 51502 : GP 0 K-40

High quality soft grease formulated with lithium soap and Extreme Pressure, anti-wear, anti-corrosion and anti-oxidation additivation.

Provides an efficient greasing of gears : no risk of dry starts as the grease, centrifuged on the cases, falls down on the gears due to its soft consistency.

Good anti-rust and anti-corrosion protection.

Excellent pumpability at cold temperatures.

Very high performance under heavy load.

PROPERTIES

Color	Visual	Dark brown
Consistency grade	DIN 51818	NLGI 0
Soap		Lithium
Penetrability - 60 cycles	ASTM D217	355 / 385 x 10-1 mm
Drop point	ASTM D2265	180 °C / 356 °F
4 Ball test	ASTM D2596	2600 N
Anti-corrosion EMCOR	IP 220	0 / 0

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty. Made in FRANCE

MOTUL - 119 Bd Félix Faure - 93303 - AUBERVILLIERS CEDEX - BP 94 - Tel: 33 1 48 11 70 00 - Fax: 33 1 48 33 28 79 - www.motul.com