



MOTUL SPECIFIC 506 01 0W-30

VOLKSWAGEN Gasoline and Diesel engine oil
Approved VW 506 01 & 506 00 & 503 00
Synthetic Technology

TYPE OF USE

Synthesis technology fuel-efficient engine oil especially for diesel engines with pump-nozzle injection technology with extended service interval.

PERFORMANCES

PERFORMANCES VW 506 01 506 00 503 00

Synthetic Ester base stocks and specific anti-friction additivation provide an outstanding oil film resistance, reducing friction in the engine, maintaining the oil pressure, and generally decreasing the operating temperature.

This Synthese-Technologie engine oil has been formulated, developed and tested according to the most recent technical requirements requested by VOLKSWAGEN.

MOTUL SPECIFIC 506 01 506 00 503 00 0W-30 provides outstanding lubricating properties such as wear and high temperature resistance and controlled oil consumption.

Anti-oxidation, Anti-wear, Anti-corrosion, Anti-foam properties.

RECOMMENDATIONS

Drain interval: according to manufacturers' recommendations and tune to your own use.

Do not mix with non VW 506 01 506 00 503 00 approved oils.

Before use always refer to the owner manual or handbook of the vehicle.

PROPERTIES

Viscosity grade	SAE J 300	0W-30
Density at 20°C (68°F)		0.851
	ASTM D445	54.1 mm ² /s
Viscosity at 40°C (104°F)		

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty.

MOTUL Deutschland GmbH - Butzweilerhofallee 3 - 50829 - Köln - +49(0)221/67003-0 - +49(0)221/67003-199 - info@motul.de - http://www.motul.com

motul.com



MOTUL SPECIFIC 506 01 0W-30

VOLKSWAGEN Gasoline and Diesel engine oil
Approved VW 506 01 & 506 00 & 503 00
Synthetic Technology

Viscosity at 100°C (212°F)	ASTM D445	9.7 mm ² /s
HTHS viscosity at 150°C (302°F)	ASTM D4741	3.1 mPa.s
Viscosity Index	ASTM D2270	166.0
Pour point	ASTM D97	-45.0 °C / -49.0 °F
TBN	ASTM D2896	10.3 mg KOH/g
Flash point	ASTM D92	218.0 °C / 424.0 °F

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty.