



## MOTUL SPECIFIC 952-A1 0W-20



**Diesel engine oil – FORD  
Synthese-Technologie**

### TYPE OF USE

High Performance Synthese-Technologie **“Fuel Economy”** lubricant specially designed for FORD vehicles with 1.5 l Diesel engine (EcoBlue).

Suitable for engines requiring a 0W-20 viscosity “Fuel Economy” lubricant with ACEA C5 standard.

Compatible with exhaust gas aftertreatment systems.

### PERFORMANCES

STANDARDS                      ACEA C5  
    WSS-M2C952-A1

MOTUL SPECIFIC 952-A1 0W-20 delivers outstanding oil film resistance, while facilitating cold start, reducing friction in the engine, maintaining the oil pressure and lowering engine operating temperatures.

Through its exceptional lubricating properties, MOTUL SPECIFIC 952-A1 0W-20 provides high level of wear resistance, high temperature and oxidation resistance. It reduces the formation of deposits, reduces wear and enables perfect control of oil consumption.

Anti-wear, anti-corrosion, anti-foam properties.

**Environment friendly, this type of oil allows fuel consumption reduction and therefore minimizes greenhouse gases (CO2) emissions.**

### RECOMMENDATIONS

Drain interval: According to manufacturers’ recommendations and to be adapted to your own use. MOTUL SPECIFIC 952-A1 0W-20 can be mixed with other synthetic oils that claim FORD WSS-M2C952-A1 specification .

Always refer to the owner manual of the vehicle before use.

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty.



## MOTUL SPECIFIC 952-A1 0W-20



Diesel engine oil – FORD  
Synthese-Technologie

### PROPERTIES

Density at 20°C (68°F)		0.839
		40.1 mm <sup>2</sup> /s
Viscosity at 40°C (104°F)		8.1 mm <sup>2</sup> /s
Viscosity at 100°C (212°F)		
HTHS viscosity at 150°C (302°F)	ASTM D4741	2.7 mPa.s
	ASTM D2270	181.0
Viscosity Index		-42.0 °C / -44.0 °F
Pour point		
Sulfated Ash		% weight
		0.77
TBN		9.4 mg KOH/g
Flash point		199.0 °C / 390.0 °F

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty.

04/24