



SPEED A 5

SPINDLE LUBRICANT

TYPE OF USE

SPEED A 5 is a premium oil for the lubrication of machine tool spindles and high-speed bearings.

PERFORMANCES

STANDARDS ISO 6743-2 L-FD / TR 3498 L-FD and L-HM

SPEED A 5 is recommended for the lubrication of high-speed spindles bearings, airline oilers, hydraulic systems requiring low-viscosity lubricants in grinders and other machine tools.

SPEED A 5 meets the following requirements:

- ISO TR 3498: L-FD and L-HM
- ISO 6743-2: L-FD

PROPERTIES

Density at 20°C (68°F)	ISO 12185	0.845
Viscosity at 40°C (104°F)	ASTM D445	5.1 cST
Viscosity at 100°C (212°F)	ASTM D445	1.6 cST
Pour point	ASTM D97	-46.0 °C
4 Ball test - Wear scar	ISO 20.623	0.54 mm
Copper Strip Corrosion	NTF M 07105	1a
Foam, Seq I, II, III	NF T 60 129	40/0-10/0-30/0 mL/mL
Flash point	ASTM D92	140.0 °C

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty.

MOTUL - 119 Bd Félix Faure - 93303 - Aubervilliers Cedex - BP 94 - FRANCE - Tel: 33 1 48 11 70 00 - Fax: 33 1 48 33 28 79 - www.motul.com

motul.com

07/24