

MOTUL STABILIZER

Gasoline shelf life improver additive
Protects gasoline fuel against oxidation
Stabilize gasoline fuel for up to 24 months
Gasoline engines - 4 & 2 Stroke

TYPE OF USE

MOTUL® STABILIZER is a gasoline shelf life improver additive to be added directly to gasoline.

It stabilizes gasoline fuel until 24 months and its unique multipurpose formulation:

- protects gasoline from oxidation, thus avoiding varnish and gums build-ups inside carburettor and making easier start up after wintering
- avoids deposits build-up in fuel injection systems, injectors, carburettors, combustion chambers and on valves
- cleans valves to restore optimum engine performance

Suitable for all kind of gasoline engines needing to be stored for a long period of time: historic vehicles, boat engines, motorcycles, ATV, UTV, scooters or snowmobile engines, gardening engines,...etc.

PERFORMANCES

Thanks to its specific formulation, MOTUL® STABILIZER:

- Protects gasoline fuel against oxidation until 24 months
- Prevents and cleans deposits on valves
- Cleans fuel injection systems, injectors and carburettors
- Maintains cleanliness of the entire fuel system by avoiding varnish and gums accumulation
- Compatible with all type of gasolines, with or without Ethanol, leaded or unleaded
- Compatible with all type of 2 Stroke gasolines, including premix fuels
- Compatible with catalytic converters

RECOMMENDATIONS

Squeeze the desired amount of MOTUL® STABILIZER into the dosing area of the bottle (see scale on the dosing head).

Add the measured amount directly into the gasoline tank before refuelling.

The fuel will then be protected, and the entire fuel system will be completely cleaned, from the tank to the injector, or carburettor, and the combustion chamber.

A full 250ml bottle can treat between 100 and 200 L of gasoline.

- Normal dosage: 250 ml for 200 L of gasoline (1:800 or 0.125%)

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty.



MOTUL STABILIZER

Gasoline shelf life improver additive
Protects gasoline fuel against oxidation
Stabilize gasoline fuel for up to 24 months
Gasoline engines - 4 & 2 Stroke

- Intensive dosage: 250 ml for 100 L of gasoline (1:400 or 0.25%)

Do not exceed the prescribed dose.

Dangerous. Observe the precautions for use.

STABILIZER is recommended for use:

- at normal dosage: at each refuelling

- at wintering: run the engine with MOTUL® STABILIZER added to gasoline in order to provide anti oxidation protection everywhere inside the fuel system and engine prior to storage.

PROPERTIES

Density at 20°C (68°F)	ASTM D4052	0.811
Flash point	ASTM D93	61.0 Above °C / 142.0 Above °F

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty.

05/26



MOTUL STABILIZER

**Gasoline shelf life improver additive
Protects gasoline fuel against oxidation
Stabilize gasoline fuel for up to 24 months
Gasoline engines - 4 & 2 Stroke**

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty.

05/26

MOTUL Deutschland GmbH - Butzweilerhofallee 3 - 50829 - Köln - +49(0)221/67003-0 - +49(0)221/67003-199 - info@motul.de - http://www.motul.com

motul.com