

**SUPRA SLIDE 220****Slideway Oil  
Mineral****TYPE OF USE****SUPRA SLIDE 220** is a high performance oil for the lubrication of machine tool slideways.**PERFORMANCES**

**STANDARDS** CINCINNATI Lamb P-47 / P-50 / SH/T0361-94 Chinese National Specification for slideway oils  
DIN 51 517 - 3 CLP / 51 524 - 2 HLP

**SUPRA SLIDE 220** is specifically designed to meet requirements for low friction, good dampening properties, excellent demulsibility and protection of precision machine tools. It is also suitable for moderate applications such as hydraulic and gear drive fluids.

**SUPRA SLIDE 220** is recommended for vertical slideways.

**SUPRA SLIDE 220** meets the following requirements:

- Cincinnati Lamb P-47 / P-50
- SH/T0361-94 Chinese National Specification for slideway oils
- DIN51524-2 HLP
- DIN51517-3 CLP

**PROPERTIES**

Density at 20°C (68°F)	ISO 12185	g/mL 0.893
Viscosity at 40°C (104°F)	ASTM D445	219.0 mm <sup>2</sup> /s
Viscosity at 100°C (212°F)	ASTM D445	19.0 mm <sup>2</sup> /s
Viscosity Index	ASTM D2270	96.1
Pour point	ASTM D97	-12.0 °C
4 Ball test - Wear scar	ISO 20.623	0.43 mm
Flash point	ASTM D92	286.0 °C

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty.