

SUPRA SLIDE 68**Slideway Oil
Mineral****TYPE OF USE**

SUPRA SLIDE 68 is a high performance oil for the lubrication of machine tool slideways.

PERFORMANCES

STANDARDS CINCINNATI Lamb P-47 / P-50 / SH/T0361-94 Chinese National Specification for slideway oils
DIN 51 517 - 3 CLP / 51 524 - 2 HLP

SUPRA SLIDE 68 is specifically designed to meet requirements for low friction, good dampening properties, excellent demulsibility and protection of precision machine tools. It is also suitable for moderate applications such as hydraulic and gear drive fluids.

SUPRA SLIDE 68 is recommended for horizontal slideways.

PROPERTIES

Density at 20°C (68°F)	ISO 12185	g/mL 0.879
Viscosity at 40°C (104°F)	ASTM D445	70.0 mm ² /s
Viscosity at 100°C (212°F)	ASTM D445	8.9 mm ² /s
Viscosity Index	ASTM D2270	100.0
Pour point	ASTM D97	-15.0 °C
4 Ball test - Wear scar	ISO 20.623	0.43 mm
Flash point	ASTM D92	248.0 °C

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty.