



SUPRACAL 32

HEAT TRANSFER

PARAFFINIC MINERAL OIL

DESCRIPTION

SUPRACAL 32 is a special high-quality oils for heat transfer and thermal regulation based on highly refined mineral oils.

APPLICATIONS

Highly refined mineral oil with paraffinic tendencies for heat transfer and thermal controls operating at temperatures up to 250°C.

SUPRACAL 32 can be used for dynamic circulation as well as static applications. Thanks to its fluidity, **SUPRACAL 32** is suitable for :

- Installations operating in closed circuits up to 270 °C with an expansion chamber
- Thermoregulators

ADVANTAGES

- Based on highly refined mineral oils.
- High temperature and oxidation stability.
- Usage up to 270 °C in closed tanks.
- Excellent anti-rust, anticorrosion and anti-foam characteristics.
- Long service life without deposit formation or viscosity increase.
- Very low vapour pressure.
- Toxic-free

**TECHNICAL INFORMATION**

TECHNICAL CHARACTERISTICS	UNITS	METHOD	SUPRACAL 32
Aspect	-		Clear
Color	-	Visual	Yellow
Density	-	ISO 12185	0,866
Viscosity at 40°C	mm ² /s	ASTM D445	30.4
Viscosity at 100°C	mm ² /s	ASTM D445	5.3
Viscosity index	-	ASTM D2270	115.0
Flash point	°C	ASTM D92	216.0
Pour point	°C	ASTM D97	-21.0
Operating range temperature	-		-10°C to +270°C
Aniline Point	°C	ASTM D611	98.9
Vapour pressure at 300°C	mbar		54.0
Specific heat at 40 °C	J/g.K	ASTM E 1269	2.4
Specific heat at 100°C	J/g.K	ASTM E 1269	2.5
Specific heat at 150 °C	J/g.K	ASTM E 1269	2.7
Specific heat at 250 °C	J/g.K	ASTM E 1269	3.0
Thermal conductivity at 20°C	W/m.K		0.1

These characteristics are given only for information and can be updated over time.

SERVICES AND EQUIPMENT

In addition to its product ranges, MotulTech can provide tools and services for the maintenance and monitoring of your lubricants. Please contact your technical sales representative for more information.



Important Notice

Information disclosed in this technical data sheet is based on MOTUL's experience and know-how in the development and manufacture of lubricants and other chemical products according to the current state of knowledge.

Any chemical product must be used in the intended application and in accordance with the recommendations provided in its safety data sheet freely consultable via the site <https://www.quickfds.com/fr/>. The performance of our products may be influenced by a series of factors, including conditions of use, application methods, operational environment, pretreatment of components, possible external contamination, etc ... For these reasons, universal recommendation of our products is impossible. The information in the technical data sheet represents general, non-binding guidelines and is given for guidance only. No express or implied warranty is given regarding the properties of the product or its suitability for a given application.

Therefore, we recommend consulting an application engineer to discuss application conditions and product performance criteria before use. It is the user's responsibility to test the functional suitability of the product and to use it under appropriate safety conditions. Our products are subject to continuous improvement with the aim of improving performance or bringing them into compliance with any new and possible regulations concerning them. We reserve the right to change our product lines, our products and their manufacturing processes and any provisions of our publications at any time without notice. This technical sheet cancels and replaces all previous editions.

We expressly draw the attention of any user to the fact that our product has not been designed and tested for use in the field of aeronautics as an "onboard" product or in the field of nuclear power production. Any use that may be made of the product in one of the aforementioned sectors will be under the exclusive responsibility of the user. Any reproduction, whatever its form, requires the prior written consent of MOTUL. All rights reserved.